

1. Vendor Information

- Vendor Name: BILLINGS PETERBILT, INC.
- Contact Person: DAN WEIMER
- Address: 3255 N. FRONTAGE RD, BILLINGS MT, 59101
- Phone Number: 406-252-5667
- Email Address: dweimer@jgpete.com

2. Sourcewell Contract Information

- Sourcewell Contract Number: 032824
- Contract Expiration Date: 2028

3. Pricing 3 V'S PLOW TRUCK

- Unit Price (per truck): \$384,920.00
- Quantity: 3 Units

Include all applicable fees (delivery, setup, etc.):

4. Estimated Delivery

- Estimated Delivery Date: JUNE 2027 UPON APPROVAL IN NO LONGER THAN 2 WEEKS

5. Service & Support

Provide details regarding guarantees or estimated timeframes triage of trucks in terms of diagnosis and parts ordering (ex. Can diagnose and order parts within 48 hours) Provide as separate attachment.

6. Attachment A

- Completed Attachment A Included:
☒ Yes ☐ No

Completed by: DAN WEIMER Date: 8-28-29

Specification Requirement	Dealer Acknowledgement (Yes/No)	Please Check if Dealer Installed option	Page/Section Location
Basic Truck Configuration			
1. All trucks will be delivered on the same date	YES		
2. Day Cab Configuration	YES		PG- 9/ 6700000
3. 48 state and Canada compliant emissions	YES		PG- 5/ 2140200
4. Left hand steering	YES		
5. Assembled in the USA	YES		E E S
6. Must have local dealer support	YES		BILLINGS PETERBILT, INC.
a. Must be within 50 miles of Yellowstone County Shop	YES		
7. Will be for three (3) completely identical trucks	YES		
8. Will be white in color	YES		
9. All lighting will be LED	YES		
10. Exhaust must exit behind and above the cab	YES		
11. Gear ratios must allow truck to run at least 72mph and the rear axle ratio should be no less than 3.73	YES		
12. Hood must be assembled in such fashion to allow access if plow is installed and in the up most position	YES		PG- 10/ 7851100
13. Aluminum Wheels	YES		PG- 8/ 5211600,5311470
Engine-minimum allowable specifications			
1. 15L Cummins Engine	YES		PG- 5/ 2059213
2. Must make 550hp @ 1600rpm	YES- 565@1900		
3. 2050lb-ft @ 1250rpm	NO 1850 LB-FT		LAST PAGE EXPLANATION
4. Block heater	YES		PG- 6/ 2521090
5. Metal drain pan	YES		
6. Magnetic drain plug	YES		
7. Multistep engine brake	YES		PG-6/ 2812170
8. 160amp alternator	YES		PG-6/ 2513060
9. Air compressor must make at least 35 CFM at 1000 engine rpm	YES		PG-6/ 2725270
Transmission			
1. Automatic transmission prefer Allison	YES		PG-7/ 4052970
a. 4500 rugged duty series	YES		PG-7/ 4052970
2. Gear selector must be mounted to the right of drivers seat on dash or column	YES		PG-7/ 4256920
3. PTO driven hydraulic pump	YES		
4. Must be able to remain activated while vehicle is in motion at highway speeds	YES		
Front axle			
1. Tire size 425/65R22.5 Bridgestone M810 20 ply rating or equal	YES		PG-8/ 5004060
2. 19000lbs minimum load rating	YES		
3. Heavy duty steering gear	YES		PG-3/ 1243050
4. Disc brakes	YES		PG-3/ 1354850, 1354870
5. Steel spring suspension	YES		PG-3/ 1114030
6. All moving points must be greaseable	YES		PG-3/ 1380070
7. Set forward design	YES		PG-9/ 6515770
Rear axles			
1. 46,000lbs minimum load rating	YES		PG-3/1526120
2. Spring style suspension	YES		
a. Henderson HMX 460	YES		PG-4/ 1824410
3. Disc brake system	YES		PG-4/ 1616305, 1616310
4. Differential lock on both axles	YES		PG-4/1687090
a. Dash mounted switches with indicators	YES		
b. Auto release above 25 mph	YES		PARAMETER
5. Tire pressure monitoring system	YES		PG-4/ 1683245
6. Rear tire size 11.00R 24.5 14 ply Bridgestone or equal	YES		PG-8/ 5104750

Specification Requirement

Dealer
Acknowledgement
(Yes/No)

Please Check if Dealer
Installed option

Page/Section Location

Frame

1. Will be constructed of steel	YES		PG-2/ 0514000
2. Smallest allowable will be 10.75" X 3.5" X .375"	YES		PG-2/ 0514000
3. Major crossmembers must be steel construction	YES		PG-2/0613200
4. Single wall construction preferred	YES		PG-2/ 0514000

Rear Hitch

1. Rated load capacity 60,000 lbs	YES		
2. Air compensated pintle hitch	YES		
3. Plumbed for trailer brakes	YES		
4. Standard 7 way industrial plug for lighting	YES		
5. Standard chip spreader bar	YES		
a. 12 inch opening	YES		
b. 1 1/4 inch diameter bar	YES		
c. 12 inches to center of bar to ground level	YES		
d. Center line of bar must be at 20" +/- 1" from the rear lip of box	YES		

Battery

1. Externally mounted preferred if room permits	YES		PG-8/ 6010670
2. Battery Shutoff	YES		

Fuel tank

1. Mounted on driver side	YES		PG-8/ 5602135
2. 125 us gallon capacity	YES		PG-8/ 5554340
3. Aluminum	YES		PG-8/ 5554340
4. External Mounted Batteries (If not tank, then else where external)	YES		PG-8/ 6010670
5. Heated fuel tank and fuel filter (Artic Fox and Davco 382)	YES		PG-8/ 5652000 PG-6/ 2921130

DEF tank

1. Mounted on driver side	YES		PG-8/ 5652890
---------------------------	-----	--	---------------

Rear fender requirements

1. One set of mudflaps will be installed at rear of the drive wheels	YES		ON BODY
2. One set of mudflaps will be installed in front of drive wheels	YES		FROM FACTORY

Internal cab requirements

1. Vocational style cab with rear window	YES		PG-10/ 7210540
2. Top tier HVAC system	YES		PG-10/ 7322010
3. Premium cab sound insulation	YES		PG- / 5401 0 540 0
4. Premium instrument cluster	YES		PG-11/ 8070830
5. Air suspension cab	YES		PG-10/ 7852020
6. Driver's seat will be premium high back black or grey cloth air suspension seat	YES		PG-9/ 6913200
a. Heavy duty seat cover included	YES	YES	
7. 18-inch diameter driver's wheel will be fully adjustable	YES		
8. Left- and right-hand electronic door locks	YES		PG-10/ 7230360
9. Power Windows	YES		PG-10/ 7230360
10. Power left and right hand heated mirrors	YES		PG-10/ 7514010
11. Passenger single passenger seat	YES		PG-9/ 6921740
12. Convex mirrors on both right and left side	YES		PG-10/ 7514010
13. Driver and passenger side sun visors	YES		PG-10/ TOP HIGHLIGHTED
14. Standard pedal configuration	YES		
15. From drivers seat full instrumentation must be visible	YES		
16. AM/FM/Bluetooth radio	YES		PG-10/ 7722120
17. 40 channel CB radio factory installed	YES		PG-10/ 7740220
18. Must be wired for additional radio to be installed by the purchasing party	YES	YES	
a. Must have constant 20 amp power supply	YES	YES	

Specification Requirement	Dealer Acknowledgement (Yes/No)	Please Check if Dealer installed option	Page/Section Location
---------------------------	---------------------------------	---	-----------------------

b. Must have ignition switched 5-amp supply	YES	YES	
c. Must be routed to a central location for mounting of additional radio	YES	YES	
19. Two (2) cab top mounted LED strobe lights on each side of cab	YES		PG-12/ 8132215
20. Externally mounted grab handles on both sides of cab to assist in entering cab	YES		PG-10/ 7110680
21. All weather rubber style floor covering	YES		STANDARD OPTION
22. 10 lb dry fire extinguisher mounted securely inside driver's side door	YES		PG-11/ 7900320
22. Engine fresh air system must be adaptable to winter applications	YES		PG-6/ 3281290
a. Must be able to draw warm air from engine compartment during plowing operations	YES		PG6/ 3281290

Sander/ Dump Box

1. Stainless Steel	YES		
2. Dual Purpose 16' live bottom with bolt on conveyor covers	YES		
3. 1/4" minimum floor thickness	YES		
4. Front discharge	YES		
5. Spinner mounted drivers side behind cab outside of frame rail	YES		
6. Rear facing tail and brake lights two per side	YES		

Snowplow

1. 12 foot straight Heinke Parallel lift plow V2.0	HENDERSON PLP	YES		
2. Full compression trip breakaway		YES		
3. Reversible		YES		
4. Extendable right side with mailbox cutout		YES		
5. 42 inch height		YES		
6. Kagi innovations wingline laser plow guide		YES		
7. Parallel lift with quick attach system		YES		

Light Package

1. All Led	YES		
2. Two clear rear side facing at 5 and 7 positions flood lights	YES		
3. Two clear forward facing at 10 and 2 position flood lights	YES		
4. Two per side tail light/brake light	YES		
5. Two rear facing green/yellow LED strobes	YES		
6. Two hood mounted forward facing Headlights	YES		
a. Heated with high/low beam and turn signal	YES		

Air equipment

1. Must be able to accommodate the 35 CFM requirements of the air compressor	YES		PG-6/ 2725270
2. Require twin air dryer setup	YES		PG-7/ 4510340
3. Will be heated	YES		
4. Pull cables drains on all air tanks	YES		

Warranty

1. Factory or dealer covered warranty	YES		
2. For a term no less than 5 years or 200,000 miles from date of delivery to Yellowstone County Shop	YES		
3. Must cover engine and drive train	YES		
4. All electrical parts due to failure	YES		
a. Item failure do to misuse will be excluded	YES		
5. All emissions must be covered for no less than 5 years also "No exceptions"	YES		
6. Everything installed by the manufacture or dealer prior to delivery will be covered by the warranty with said exceptions	YES		
a. Wheels and tires	YES		
b. Brakes	YES		

Specification Requirement	Dealer Acknowledgement (Yes/No)	Please Check if Dealer installed option	Page/Section Location
c. Glass items	YES		
i. Windshields	YES		
ii. Back windows	YES		
iii. Side windows	YES		
iv. Mirrors	YES		
4. Belts	YES		
5. Hoses	YES		
7. It will be the responsibility of Yellowstone County to deliver the trucks to the dealer for repairs	YES		
8. When these 3 trucks are brought in for warranty repairs, they must be diagnosed and have parts ordered within 24 hours of arrival to dealer location	YES		
i. This will be in writing and provided with all the documentation for the trucks	YES		
9. Must be provided with a complete parts book and shop repair manual	YES		
i. Can be printed or digital	YES		
ii. Can be online accessible for a period of 10 years	YES		

Explanation on the engine section for the 2050 lb torque that i had to put a "NO" on- Allison does not allow any of their transmissions to be installed behind a motor of any brand with 2050 torque rating. In their brochure they point out it will take that torque, but they do not allow any manufacturer to install it in in thier chassis with a 2050 torque rating.



BILLINGS PETERBILT, INC.

3255 N FRONTAGE ROAD • BILLINGS, MT 59101 • PHONE (800) 548-7565

STOCK #
TBD

DATE:
8/28/2026

VEHICLE BUYER'S ORDER AND PURCHASE AGREEMENT

PURCHASER'S NAME				RES OR BUS PHONE		CELL PHONE	
YELLOWSTONE COUNTY ROAD AND BRIDGE							
ADDRESS				CITY		STATE	ZIP
3321 KING AVE E				BILLINGS		MT	59101
NEW/USED	YEAR	MAKE	MODEL	VIN/Quote #		COLOR	
NEW	2027	PETERBILT	567	TBD		WHITE	
				TRADE INFORMATION		RETAIL PRICE W/ OPTIONS	
				YEAR		BODY	
2027 PETERBILT WITH 3 V'S PLOW				MAKE		FET	
SYSTEM				MODEL		EXTENDED WARRANTY	
				COLOR			
AS REQUESTED BY BID SPEC WITH				MILEAGE		SUBTOTAL	
ALL WARRANTIES				SLEEPER		STATE TIRE TAX	
				ENGINE		STATE SALES TAX	
						LICENSE & REGISTRATION	
				TRADE PAYOFF TO WHOM		DOC FEE	
						TOTAL	
						TRADE ALLOWANCE	
						PAYOFF	
				PHONE #		EQUITY	
				ACCT #		QUANTITY	
				PAYOFF		DEPOSIT	
				GOOD UNTIL		DOWN PAYMENT	
						BALANCE DUE	
						384,215.00	
				Purchaser agrees to be responsible for any manufacturing surcharges applied after the order date (see item 7 below)			
				Purchaser agrees that this agreement (the "Agreement", together with the reverse side hereof, is entered into between it and BILLINGS PETERBILT, INC. ("DEALER"), that this Agreement cancels and supersedes any prior agreement between the forgoing parties, that as of the date hereof, comprises the complete and exclusive statement of the terms of the agreement relating to the subject matters covered hereby, and that THIS AGREEMENT SHALL NOT BECOME BINDING UNTIL ACCEPTED BY DEALER OR DEALER'S AUTHORIZED REPRESENTATIVE. Purchaser by execution of this agreement, acknowledges that Purchaser has received copy of the agreement, has read and understands the terms and conditions hereof, and has voluntarily entered into the same.			
TOTAL WARRANTY							
NO VERBAL ORDERS-THIS IS COMPLETE AGREEMENT							
PURCHASER'S SIGNATURE				DATE			
NOT VALID UNLESS ACCEPTED BY MANAGEMENT				DEALER OR HIS AUTHORIZED REPRESENTATIVE			
VERSION CONTROL: 2/1/2025				NOT VALID UNLESS ACCEPTED BY MANAGEMENT			

-General Terms and Conditions-

The Purchaser and Dealer further understand and agree that, coupled with terms and conditions provided on page 1, the following terms and conditions govern the subject matter of this Vehicle Buyer's Order and Purchase Agreement (hereinafter "Agreement"):

1. Purchaser agrees to purchase the vehicle(s) listed on the front page of this Agreement within five (5) days of signing this Agreement or in the case of special ordered vehicle(s) (defined in paragraph 2), within five(5) days of receipt of said vehicle(s) by Dealer. This Agreement is non-cancellable for any reason.
2. Any vehicle(s) not in the Dealer's inventory as of the date of this Agreement are defined herein as special ordered vehicles and are referred to herein as SOV(s). SOV(s) are non-cancellable for any reason. SOV(s) also include all hybrid and electric vehicle(s).
3. Purchaser shall deliver the original bill of sale and the title to any used vehicle traded herein along with the delivery of such vehicle in the same condition containing the same equipment as when appraised, reasonable wear and tear excepted, and the Purchaser warrants such vehicle to be his property free and clear of lien and encumbrances except as otherwise disclosed to Dealer on the front page hereof. If no trade is listed on the front page of this Agreement, then no trade will be accepted by Dealer.
4. The failure or refusal of the Purchaser to complete the purchase contemplated herein shall be a material breach of this Agreement and Dealer shall be entitled to all rights and remedies under the law, including, but not limited to, lost profits, damages, specific performance and its attorney fees and court costs. The Purchaser agrees, that in addition to any other legal remedy available to Dealer, any deposit provided to Dealer shall be retained and forfeited to Dealer, and/or in the event a used vehicle has been taken in trade, the Dealer may sell said used vehicle, and the Dealer shall be entitled to reimburse itself out of the proceeds of such sale, to cover its expense and losses incurred or suffered as the result of Purchaser's failure to complete said purchase.
5. The manufacturer has the right to make changes in the model or design of any accessories and part of any new motor vehicle at any time without creating an obligation on the part of either the Dealer or the manufacturer to make corresponding changes in the vehicle covered by this Agreement either before or subsequent to the delivery of such vehicle to the Purchaser. Purchaser agrees to accept the vehicle as manufactured and delivered, even if specific parts or components are not installed or not available at delivery.
6. In no event, shall Dealer be liable for delays or failure to deliver the vehicle on a specified day, including delays caused by the manufacturer, accidents, sureties, fires or other causes or acts beyond the control of the Dealer. Any delays caused by pandemics, war, shortages, civil unrest or similar circumstance are at Purchaser's risk.
7. From time-to-time manufacturer surcharges are added to the vehicle(s) listed on the front page of this Agreement. Purchaser agrees to be responsible for any such surcharges at the time of delivery. Surcharges amounts will be added to the final invoice and documentation supporting surcharges will be provided to the Purchaser.
8. NO WARRANTIES EXPRESSED OR IMPLIED, ARE MADE OR WILL BE DEEMED TO HAVE BEEN MADE BY EITHER THE DEALER OR THE MANUFACTURER OF A MOTOR VEHICLE OR MOTOR VEHICLE CHASSIS PURCHASED HEREUNDER, vehicle on a specified day, including delays A COPY OF WHICH WILL BE DELIVERED TO PURCHASER. AT THE TIME OF DELIVERY OF A MOTOR VEHICLE OR MOTOR VEHICLE CHASSIS, SUCH WARRANTY SHALL BE EXPRESSLY IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND THE REMEDIES SET FORTH IN SUCH WARRANTY WILL BE THE ONLY REMEDIES AVAILABLE TO ANY PERSON WITH RESPECT TO SUCH MOTOR VEHICLE OR MOTOR VEHICLE CHASSIS.
NO WARRANTIES, EXPRESS OR IMPLIED, ARE MADE BY THE DEALER WITH RESPECT TO USED MOTOR VEHICLES OR MOTOR VEHICLE CHASSIS FURNISHED HEREUNDER EXCEPT AS MAY BE EXPRESSED IN WRITING BY THE DEALER FOR SUCH USED MOTOR VEHICLE OR MOTOR VEHICLE CHASSIS, WHICH WARRANTY, IF SO EXPRESSED IN WRITING.
9. In case the vehicle covered by this agreement is a used or demonstrator vehicle, no warranty or representation is made as to how such vehicle has been used, regardless of the mileage shown on the speedometer of said used vehicle.
10. In the event that it becomes necessary for the Dealer to enforce any of the terms and conditions of the agreement, Purchaser agrees to pay reasonable attorney's fees and court costs, including collections costs.
11. All past due amounts and payments due to Dealer hereunder shall bear interest at the rate of eighteen (18%) percent per annum.
12. This agreement is non-transferable by the Purchaser nor may any of Purchaser's rights or obligations hereunder be assigned. Dealer may assign all of its rights and obligations hereunder, including to its Affiliates, upon reasonable notice to Purchaser.
13. LIABILITY INSURANCE COVERAGE FOR BODILY AND DAMAGE CAUSED TO OTHERS IS NOT INCLUDED IN THIS AGREEMENT.
14. PURCHASER REPRESENTS THAT he/she is 18 years of age or older at the time of the consummation of the purchase hereunder. Purchaser further represents that if it is ordering electric vehicle(s) it has the ability to charge said vehicle(s) and is not relying on Dealer to provide charging services.
15. Title/MSO to the vehicle shall remain with the Dealer until purchase price is paid in full; and, until such payment is paid in full, Purchaser hereby grants to Dealer a security interest in the subject vehicle for the purpose of securing payment therefore.
16. No agreement, verbal or otherwise, not contained in this agreement will be recognized.
17. In case of the vehicle covered by this agreement is a used vehicle, the information you see on the window form (Buyer's Guide) for this vehicle shall be made part of this Agreement. Provided, any terms or conditions on such window form which conflict with the terms and conditions of this Agreement, shall govern.
18. The parties agree the term "DEPOSIT" (as used herein) means any deposit paid by the Purchaser to secure, order, or hold Vehicle(s) from Dealer., or its Affiliates. Deposit made by Purchaser is non-refundable.
19. Federal Excise Tax will be remitted on the vehicle(s) listed on the front page of this agreement. Purchaser agrees any additions added to the vehicle(s) and not listed on the front page of this agreement which are subject to said tax will be reported to and paid directly by the Purchaser to the Internal Revenue Service.
20. Purchaser is solely responsible to conduct its own due diligence when determining engine size, torque ratings, tires and wheel size, and all other specifications necessary for the proper use of any motor vehicle. Purchaser is solely responsible to ensure any changes made by the manufacturer to the vehicle in the build process conforms to its uses, needs, and requirements. Dealer is not responsible for any changes between orders submitted to the manufacturer and vehicles delivered by the manufacturer. Purchaser is solely responsible for understanding emission requirements and the states' laws where it intends to operate any Vehicle(s) purchased from Dealer. Purchaser is not relying on any recommendations by Dealer as to the legality of operating any Vehicle(s) in any country, state, city or location.
21. Purchaser acknowledges, understands, and agrees that Dealer may commingle the deposit with Dealer's other funds, and that neither Dealer nor its Affiliates shall be required to place the deposit in a trust account or to pay Purchaser interest thereon.
22. For the purposes of this Agreement and all attendant documents, "Affiliates" shall mean any individual, joint venture, partnership, corporation, business entity, member or stockholder which controls, is controlled by, or is under common control with, or the management and operations of which are substantially influenced by, Dealer.
23. This Agreement is the exclusive agreement between the parties with respect to its subject matter and as of its reference date supersedes all prior agreements, negotiations, representations, and proposals, written or oral, related to its subject matter. Its terms cannot be modified, supplemented or rescinded except by an agreement in writing signed by an authorized representative of all parties. There are no conditions precedent to the effectiveness of this Agreement other than those expressly stated in this Agreement. In entering into this Agreement, neither party has relied upon any statement, representation, warranty or agreement of the other party except for those expressly contained in this Agreement.
24. In the event that any portion of this Agreement shall be held to be unenforceable, the remaining portions of this Agreement shall remain in full force and effect.
25. Except as otherwise provided in this document, this Agreement may be modified, superseded, or voided only upon the written and signed agreement of the parties.
26. This Agreement and any disputes arising out of or in connection with this Agreement shall be governed by and construed in accordance with the laws of the State of Utah except for that portion relating to conflicts of laws. Any matter involving interpretation or enforcement of this Agreement shall be brought in the state or federal courts in Salt Lake County, Utah. The parties hereby accept the jurisdiction of those courts.
27. The Dealer does not have control of additional surcharges added by the manufacturer after the order date. Any such surcharges will be passed on to the Purchaser, and documentation supporting those surcharges will be provided to the Purchaser.

(Rev. 11-30-2023)

VIN #

Make Checks Payable to BILLINGS PETERBILT, INC.

Deposit Amount: \$

Customer Company Name

BILLINGS PETERBILT, INC.

Signature

Signature

Date

Date

VERSION CONTROL: 2/1/2025



Jackson Group Peterbilt – Billings (M550)
3255 N. Frontage Road
Billings, Montana 59101

YELLOWSTONE COUNTY ROAD & BRI
3321 KING AVE E
BILLINGS, Montana 59101
United States of America

Dan Weimer
Cell Phone:
Office Phone: 406-252-5667
Email: dweimer@jgpete.com

GREG FISHER

Vehicle Summary

Unit		Chassis	
Model:	Model 567	Fr Axle Load (lbs):	20000
Type:	Full Truck	Rr Axle Load (lbs):	46000
Description 1:	PLOW TRUCKS	G.V.W.R. (lbs):	66000
Description 2:		G.C.W. (lbs):	66000
Application		Road Conditions:	
Intended Serv.:	Snowplow	Class A (Highway)	95
Commodity:	Other Commodity	Class B (Hwy/Mtn)	5
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	
Type:	End Dump		6
Length (ft):	16	Wheelbase (in):	220
Height (ft):	13	Overhang (in):	55
Max Laden Weight (lbs):	8500	Fr Axle to BOC (in):	90.1
Trailer		Cab to Axle (in):	129.9
No. of Trailer Axles:	0	Cab to EOF (in):	184.9
Type:		Overall Comb. Length (in):	306
Length (ft):	0	Special Req.	
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

Price Level: January 1, 2026
Deal: PLOW TRUCKS
Printed On: 8/28/2026 11:35:49 AM

100% Complete

Date: August 28, 2026
Quote Number: QUO-1274330-P3T4V9



Sales Code	Std/ Opt	Description	\$ List	Weight
Base Model				
0005671	S	Model 567 The Model 567 is available in both a set-forward and set-back front axle configuration to provide customers with maximum versatility for their application requirements. For weight-sensitive applications, the set-forward front axle provides optimized weight distribution and compliance with bridge laws. The Model 567 has steer axle ratings up to 22,000 lbs. The 567 also offers single, tandem or tridem drive axles and a variety of lift axles for added versatility. Available with a 115" or 121" BBC and as a day cab or with a selection of detachable sleeper configurations, the 567 is as versatile as it is reliable.	214,213	14,800
0091200	S	Other Commodity	0	0
0093150	O	Snowplow Truck which is configured for mounting a snowplow to the front. May also have dump or other body.	0	0
0095170	O	End Dump Do not use for side dump bodies	0	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipso MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configuration				
0200700	S	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0514000	O	10-3/4" Steel Rails To 354" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	526	260
0611250	O	Heavy-Duty Iron Front Spring Brackets With Front Air Leaf the front spring bracket is iron but not the shackle bracket	493	35
0611330	O	Zinc Coated Anti Corrosion Treated Frame Rails Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common.	387	4
0613200	O	5-Pc Crossmembers, BOC Excludes Suspension Steel crossmember with aluminum gussets	743	14
0620571	O	Front Frame Hard Point Structure for Equipment Mounting 2.1M HD	2,827	551
0620572	O	Del PB Installed Kicker Brace For Front Frame Hard Point Structure	-264	0
0644090	O	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	60	-64
0651090	O	Omit Rear Mudflaps and Hangers	-58	-25

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
Front Axle & Equipment				
1011890	O	PACCAR FX-20 Steer Axle 20,000 lbs. 4" Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 20,000 pounds. Front axle is designed for demanding applications such as construction, heavy haul, refuse, and other vocational uses. Robust forged steel beam construction for long-lasting performance. It utilizes innovative tapered kingpin roller bearings for more efficient operation and improved steering efficiency. The PACCAR Steer Axle comes standard with the PACCAR warranty of 5 years, 750,000 miles.	2,863	137
1114030	O	Taper Leaf Springs, Shocks 20,000 lb Standard with Heavy Resistance Shocks.	741	-156
1243050	O	Power Steering Sheppard HD94 Dual Gear For use with 16,000 to 20,000 lb. axle ratings.	2,079	100
1250250	O	Power Steering Reservoir Frame Mounted w/Cooler A power steering cooler helps reduce the heat of the power steering fluid. This is commonly used with systems that may experience more stress from towing or off-road driving.	195	2
1354850	O	PHP10 Iron PreSet PLUS Hubs - Air Disc Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still offering dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear.	-65	42
1354870	O	Severe Service Disc Brake Rotor - Steer Axle	360	97
1380070	O	Greasable Front Spring Pins	67	0
1380380	S	Tenneco Shocks For Steer Axle Integrated front suspension to suit heavy duty truck market, combining the air spring and the damper into one module.	0	0
1380490	O	PACCAR FX Wide Track IPO Standard 71in KPI IPO 69in front axle for improved turning radius.	0	15
1391480	O	Pad Dust Shields for Air Disc Brakes; Front Axle Pad dust shields for air disc brakes can increase brake life. Brake dust shields reduce the buildup of road grime, extend brake system life and prevent premature failure.	51	2
1392180	O	Meritor EX+L Optimized Linehaul Air Disc Brakes Steer Axle. Meritor EX+L Optimized Air Disc Brakes with calipers that are 11 to 15 pounds lighter, per wheel end, than current EX+L brake calipers.	68	0
Rear Axle & Equipment				
1526120	O	Meritor RT46-160 46,000 lb Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD FE 75W-90 synthetic axle lube	5,163	634

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life. If code 1526120 (RT46-160) is ordered with 1680460 (Heavy Wall), you will get the 16 mm wall, but not the improved carrier that is in 1526130 code (RT46-160E) that also has a 16 mm wall. This could affect Heavy Haul service warranty length in Canada per Meritor.		
1616305	O	PHP10 Iron Preset + Hubs - Air Disc	1,715	0
1616310	O	Severe Service Disc Brake Rotor - Drive	-124	14
1660040	O	Pad Dust Shields for Air Disc Brakes, Drive Axle(s)	44	0
1673090	O	Separate Dash Controls, Cont Trac Full Lock Dana Spicer or Meritor - Tandem or Tri-Drive Axles	121	2
1680500	O	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	277	0
1680525	O	Pneumatic Park Brake	0	0
1680950	O	Stability System Not Selected Or Not Available	-6	0
1682710	S	Anti-Lock Braking System (ABS) 6S6M ABS-6. Includes air braking system.	0	0
1683245	S	Tire Pressure Monitoring System	0	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687090	O	Diff Lock Tandem Axles With Speed Interlock. Automatically Disengages Wheel Diff Lock at Speeds Above 25 mph.	2,004	60
1687175	O	Meritor EX+L Optimized Air Disc Brakes Tandem Drive. Meritor EX+L Optimized Air Disc Brakes with calipers that are 11 to 15 pounds lighter, per wheel end, than current EX+L brake calipers.	-26	0
1703730	O	Ratio 3.73 Rear Axle	0	0
1824410	O	Hendrickson HMX EX 460 46,000 LBS., 54" Haulmaax, 70K Creep Rating. Includes Traax Rod as standard, option 1920905 is not needed or available. Progressive load spring system easily adjusts to the load for an enhanced combination of empty-ride quality and loaded stability.	3,585	184

Engine & Equipment

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
2059213	O	X15 565@1900 GOV@1900 1850@1000 Performance Series (2024 Emissions)	16,695	428
		N21350 C121 68....Maximum Accelerator Vehicle		
		N21370 C128 68....Maximum Cruise Control Speed		
		N21460 C132 1400...PTO Maximum Engine Speed		
		N21520 C133 5.....Idle Shutdown Timer		
		N21610 C188 39....Idle Shutdown Cold Ambient A		
		N21620 C189 60....Idle Shutdown Intermediate A		
		N21630 C190 80....Idle Shutdown Hot Ambient Ai		
		N21550 C206 35....Idle Shutdown Percent Engine		
		N21340 C209 100...Maximum Vehicle Speed		
		N21510 C225 YES...Idle Shutdown with Parking B		
		N21450 C231 NO....Gear Down Protection		
		N21570 C233 NO....Idle Shutdown Manual Overrid		
		N21440 C234 NO....Engine Protection Shutdown		
		N21480 C238 NO....Cruise Control and Engine Br		
		N21470 C239 NO....Cruise Control Auto-Resume		
		N21430 C333 0.....Driver Initiated OverrideMax		
		N21410 C334 0.....Driver Initiated Override Ma		
		N21590 C382 YES...Idle Shutdown Hot Ambient Au		
		N21500 C395 0.....Green House Gas Automatic En		
		N21530 C396 YES...Idle Shutdown Warning Period		
		N21540 C397 60....Idle Shutdown Warning Period		
		N21320 C399 100...Green House Gas Vehicle Spee		
		N21400 C400 252...Driver Initiated Override Re		
		N21420 C401 10....Green House Gas Vehicle Spee		
		N21330 C402 0.....Green House Gas Vehicle Spee		
2091120	S	EMUX Electronics Architecture	0	0
2091305	S	Engine Idle Shutdown Timer Enabled	0	0
2091315	O	Enable EIST Ambient Temp Overrule	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091640		Effective VSL Setting NA	0	0
2092015	O	Typical Operating Speed 70 MPH	0	0
2092033	S	Powertrain Optimized for Balance Best analysis for vehicles where service includes frequent start and stop cycles.	0	0
2120160	O	TRV For DAVCO Only X15 and P-10	48	0
2140200	O	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2140410	S	Engine Brake Controls Located on RH Column	0	0
2140450	O	Remote PTO/Throttle, 12-Pin Eng Bay Remote Control Provision	135	0
2140660	O	CARB Emission Compliant Engine	0	0
2140700	S	EPA Engine Idling Compliance	0	0

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2521090	S	Immersion Type Block Heater 110-120V Standard location is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	0	0
2522090	O	PACCAR Premium Starter - X15 Engines Only PACCAR Premium 12 volt. Better cranking power, lower current draw and improved warranty to 36 months / 350,000 mi / 560,000 km.	462	0
2538040	S	3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2539716	O	CAB & SLPR POWER DISC SW MTD ON BBOX (KISSLING DISC SW 300A)	643	3
2539720	S	Low Voltage Disconnect System	0	0
2621000	O	2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	506	0
2725270	O	37.4 CFM Air Compressor X15	275	27
2812170	O	Jacobs Compression Brake ISX/ISX15/X15 Features a dedicated cam lobe design for optimum power and three-stage engine brake operation.	0	0
2921130	O	DAVCO 382 Fuel/Water Separator The Fuel Pro 382 is a combination of diesel fuel filtration and water separator that is recommended for heavy-duty diesel engines with flow rates up to 180 gallon/hour.	498	0
2921340	O	12V and 120V Heat for Fuel Filter	238	3
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 520 1242 sq in, 579 1325 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 567 1440 sq in, 589 1604 sq in.	0	0
3281290	O	Inside/Outside Air Intake Cab mounted controls	1,044	10
3291680	S	(1) Air Cleaner Firewall Mounted Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0	0

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



Sales Code	Std/Opt	Description	\$ List	Weight
3367160	S	Exhaust Single RH Side of Cab DPF/SCR RH Under Cab, Single Module	0	0
3381770	O	Curved Tip Standpipe(s)	43	1
3387870	S	24" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	0	0

Transmission & Equipment

4052970	O	Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series	29,199	528
4211520	O	SPL250 Lite HT Driveline, 1 Midship Bearing	1,562	85
4216330	O	SPL170 XL Driveline Interaxle Dana Spicer Life Series heavy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles.	802	5
4250900	O	Main Transmission Rear Support Additional rear support for the transmission to provide a firm, durable design that improves stabilization of the drivetrain in rugged terrain	124	11
4252890	O	Allison FuelSense Not Desired Dynamic Shift Sensing	0	0
4252940	O	Allison Neutral At Stop Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max packages only.	0	0
4256740	O	Allison 6-Speed Configuration, Wide Ratio Gears Allison 4500 transmission only	0	0
4256920	O	Dash Mounted Push Button Shifter Available with Allison transmissions	281	0

Air & Trailer Equipment

4510340	O	(2) Bendix AD-IS Air Dryers, Everflow Switching Module, coalescing filters	1,773	34
4520420	O	Pull Cords All Air Tanks	2	1
4540420	S	Nylon Chassis Hose	0	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
4610890	O	Body Lighting Junction Box, With Wiring Located end-of-frame	283	0
4610920	S	Self-Returning Brake Hand Valve Dash mounted controls	0	0
4612780	O	AE Connection EOF, 7-Way Socket, 4' Additional Lines coiled and strapped to frame, without gladhands	-138	15
4615250	O	Fitting For F/O Air Port	65	0

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		The furnished by owner fitting air port is mounted outboard of the driver's seat. This allows operators access to pressurize truck air, to maintain clean air in the cab.		

Tires & Wheels

5004060	O	FF: CN 20ply 425/65R22.5 HAC3 Efficiency Rating: Optimal Wide base, all-position fitment for on/off, mixed service applications. Includes TPMS sensor.	1,330	146
5104750	O	RR: CN 16Ply 11R24.5 Conti HDR2+	1,452	168
5190008	S	Code-rear Tire Qty 08	0	0
5211600	O	FF: Accur 29683SP 22.5X12.25 Alm Std Polish, 2.88" Inset	1,073	-10
5311470	O	RR: Accuride 42362SP 24.5X8.25 Aluminum Wheel Standard polish.	2,184	-136
5390008	S	Code-rear Rim Qty 08	0	0

Fuel Tanks

5554340	O	26" Aluminum 135 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	862	42
5602135	O	Location LH U/C 135 Gallon	0	0
5650490	O	Fuel Cooler Required with single fuel tank	193	15
5652000	O	(1) C450 Fuel Heater, (1) Tank Integral fuel pick-up tube	1,163	29
5652340	O	Heavy-Duty Fuel Tank Step Reinforcements	312	5
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0	0
5652980	S	DEF To Fuel Ratio Between 1:1 And 2:1	0	0
5655019	S	DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal	0	0
5760010	O	RH Tank None Furnished	-714	-86

Battery Box & Bumper

6010670	O	Aluminum Space Saver Battery Box LH BOC Battery access from side	85	-57
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0
6121090	O	Steel Bumper Deep Tapered Chromed Two tow points	-324	49
6132040	O	Omit Front Tow Pin(s)	-56	-2
6132450	O	Heavy Duty External Tow Eye	607	42

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
IPO Standard, N/A With FETPO				
Cab & Equipment				
6515770	O	Vocational 121 BBC Alum Cab and Metton Hood SFFA Stainless steel crown and grille with tilt assist.	3,756	-30
6540160	O	Thermal Insulation Package in Cab The thermal insulation package is designed to make the cab thermally efficient in extreme temperatures. The model 520 adds insulation surrounding the doghouse to reduce engine heat transmitted to the cab.	20	2
6540660	O	SmartSound Cab Insulation Package Cab acoustic insulation package for day cabs. Includes insulated inside firewall, top side floor damping, absorber treated kick panels, and insulated backwall and roof structure.	429	65
6700000	S	No Sleeper Selected	0	0
6800330	O	Rubber Fender Lips 4.5" Wide	631	6
6913200	O	National HP Driver Seat The National HP driver seat provides the latestes techonology in comfort, adjustability and ergonomic support. Includes a wide mounting base.	398	-6
6921740	S	Peterbilt ST Non-Adjustable Passenger Seat Standard vinyl, no suspension cover, no seat back recline.	0	0
6930580	O	Drivers Armrests - LH & RH	170	4
6930800	O	Black Seat Color IPO Standard Color	0	0
6931120	O	Seat Belt Color Orange IPO Standard Black	13	0
6939400	S	Air Ride Driver	0	0
6939420	S	High Back Driver	0	0
6939480	O	Mordura Driver	92	0
6939510	S	Non-Air Ride Passenger	0	0
6939520	S	High Back Passenger	0	0
6939580	O	Mordura Passenger	91	0
6939660	S	Static Riser Under Passenger Seat Peterbilt passenger non-adjustable seat.	0	0
7000025	S	Steering Wheel With Multi-Function Includes Peterbilt logo on horn button , audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.	0	0
7000045	O	High-Visibility Interior Grabhandles, Painted Bright yellow interior grabhandle for vocational vehicles.	37	0
7001520	S	Adjustable Steering Column - Tilt/Telescope	0	0
7037130	S	Prestige Interior - Sterling Gray Features single tone dash with tough, scratch resistant materials including soft touch points on top of dash. Top of dash, door panel uppers, and kick panel are charcoal to conceal dirt and mitigate wear. Includes unique technical grained A,B, C & D instrument panels with contoured doorpads, padded fabric headliner and vinyl wall panels.	0	0

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		Superior ergonomics are achieved while maximizing productivity featuring: multiple power ports, (2) coat hooks, header-mounted domelight, power lift driver and passenger windows, LH and RH door mounted map pockets with built-in courtesy lights, driver and passenger dome/reading lights and footwell lighting. Comfort features include automatic temperature HVAC controls, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, rubber flooring, (3) inside sunvisors, integrated "dead pedal, cup holder and map bin in dash.		
7110680	O	Exterior Cab Entry Grabhandle Textured; NFPA compliant. Available on Day Cab specifications only.	175	6
7210540	S	Day Cab Rear Window Day cab rear window flush to back of cab.	0	0
7210550	S	1-Piece Glass Rear Cab Window Fixed	0	0
7230060	S	1-Piece Curved Windshield	0	0
7230360	S	Power Door Locks and Power Window Lifts Standard	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7330880	O	Additional Fine Particulate Filter For HVAC Syst 3 micron filtration. For use in extreme high dust applications. Not available with Ember filter 7330890.	18	1
7514010	O	Peterbilt Aero Rear View Mirror, Motorized Includes top mirror with motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	318	3
7514020	O	Aero Rear View Mirror Housing - Body Color (Same Color as Vehicle Body)	21	0
7514050	S	Look Down Mirror Over Passenger Door with Black Housing	0	0
7610500	S	Air Horn Mounted Under Cab	0	0
7722120	O	ConcertClass, AM/FM, Weatherband, 3.5 Aux	463	10
7725740	O	Midlevel Speaker Package For Cab (4) Speakers	121	6
7728040	O	Bluetooth Phone and Audio Requires USB Port	122	0
7728050	O	USB Port	51	0
7740220	O	Uniden PC78LTX CB Radio Mounted Center Of Without weatherband.	243	10
7743020	O	(1) Antenna for Factory Installed Or F/O CB, mounted vertical center BOC/BOS.	98	1
7788335	S	Global Telematics Hardware	0	0
7851100	O	Stationary Grille w/o Fepto Extension	1,264	4
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7852020	O	Cab Air Suspension	280	15

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
7855120	O	Bugscreen - Removable External Mounted	301	2
7900090	O	Triangle Reflector Kit, Ship Loose Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	33	13
7900320	O	Fire Extinguisher, Mounted Inboard Driver Seat Hazmat approved UL listed/rated ABC	76	8
7901130	O	Backup Alarm (107 DB)	135	3
8011410	O	Drive Axle #1 Front Oil Temperature Gauge 52mm round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	96	0
8011420	O	Drive Axle #2 Rear Oil Temperature Gauge 52mm round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	109	0
8011470	O	Engine Oil Temperature Gauge 52mm round, backlit. These physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	5	0
8011850	O	Transmission Oil Temperature (Main) Located in Digital Cluster Display.	29	0
8012240	O	Guard(s) For Rear Axle Heat Gauge	69	2
8021800	S	Air Filter Restriction Pressure Gauge Located in Digital Cluster Display	0	0
8021810	S	Brake Application Air Pressure (Tractor) Located in Digital Cluster Display.	0	0
8022160	O	Fuel Filter Restriction Gauge 52mm Round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	166	0
8070100	O	(4) Additional Dash Switches With Wiring Located on dash panel C. Availability subject to dash space. Includes 4" 14 gauge wire with butt splice at rear of each additional switch.	172	1
8070250	O	Switch & Wiring For F/O Snow Plow Light Install. Switch and wiring for furnished by owner snow plow light installation. J168 on chassis harness.	101	0
8070450	O	Engine PTO Hourmeter Gauge Located In Digital Cluster Display	0	0
8070820	S	Engine Percent Torque Located in Digital Cluster Display	0	0
8070830	O	Main Instrumentation Panel Digital Cluster 15" Display includes: Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, and Voltmeter.	0	0
8071470	O	ABS Off-Road Switch Bendix ATC is required on the specification. Off-Road switch allows some wheel slippage prior to ATC activation. Off-Road switch will cause	95	0

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		the ATC light to flash, reminding the driver of a condition. Switch should only be used in extreme conditions such as snow, ice or mud.		
8071900	O	Manifold Pressure Gauge 52mm Round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	62	2
8073020	O	(4) Additional Electric Over Air Switches On/off only, switch has green indicator light, air connections on frame rail under cab. Four accessory solenoid banks with plugs.	107	2
8110070	S	Headlights Projector Module Pod Fender mounted turn signals, projector module low beam, complex reflector high beam, pod mounted	0	0
8121170	O	(5) Marker Lights, Bus LED Bullet	179	0
8131420	O	Switch & Wiring For F/O Fog Lights With bumper cutouts	165	0
8132215	O	(2) LED Strobe Lights Roof Mounted (2) LED strobe lights roof mounted on each side of the cab with stainless steel brackets. LED technology provides continual heavy-duty use in the toughest conditions with a weatherproof and vibration resistant design for external use. Offering four times the brightness in a more compact housing, 4.5" shorter and 3" smaller in diameter. Classified as a Class 1 light incandescent light.	396	10
8133960	S	Daytime Running Lights The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.	0	0
8140850	O	Moveable EOF Crossmember For Mounting Tail Lights Square end of frame with or without end of frame crossmember	51	2
8141000	O	LED Stop/Turn/Tail, Backup Flange Mounted Flange mounted. LED backup and security rings. Tapered end of frame mounted under end of frame crossmember. Mounted inset between rails.	108	28
8141150	O	Additional LED Turn Signals Mounted lower rear corners back of cab / back of sleeper	248	10

Paint

8500710	S	Standard Paint Color Selection	-200	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0	0

Shipping Destination

Options Not Subject To Discount

9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0	0
---------	---	---	---	---

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
9407147	O	Fuel Price Index Factor \$483 NET	483	0
9408626	O	SmartLINQ RD - 5YR Sub Cummins Engines	799	0
9408707	O	Base Warr: Emissions (CARB Operation) 5YR/350K MI - X15 PER/PRO Engine	3,895	0
9408982	O	Vehicle Layout Option is not subject to discount. Fleets will be split prior to build so that the charge is applied to only one unit. Quotes will not reflect this.	1,500	0
Miscellaneous				
9409001	S	Day Cab / Prestige Interior (DM)	0	0
9409076	O	State Of Registry: Montana	0	0
9409641	O	Model Year 2026 Engine	0	0
9409749	O	2024 Series Emissions Engine	0	0
9409843	O	Peterbilt Sourcewell Program Code Applicable with Marketing Programs Only. No CAR allowed	0	0
9485083	O	Basic Vehicle (CARB) 5/200 5 yrs / 200,000 mi / 320,000 km	4,905	0
9487548	O	Cummins Prtect Plan+ (5/200) CARB 2024 Series X15 Performance/Productivity	2,200	0

Promotions

Special Requirements

Special Requirement 1 0098170
Special Requirement 2
Special Requirement 3
Special Requirement 4

Fuel Efficiency Score:

Order Comments

Price Level: January 1, 2026
Deal: PLOW TRUCKS
Printed On: 8/28/2026 11:35:49 AM

100% Complete

Date: August 28, 2026
Quote Number: QUO-1274330-P3T4V9

QUOTE


Date: August 26, 2026
Estimate # -4684

Jordan VanDyke
3V Distributing
PO Box 955
Conrad MT 59425
406-278-5400
3vdist@3rivers.net
Customer ID Yellowstone
County

Salesperson	Job	Shipping Method	Shipping Terms	Delivery Date	Payment Terms	Due Date
	Dump Truck/Plow					

Qty	Item #	Description	Unit Price	Discount	Line Total
1	Henderson	16' x 36" Stainless Chain Floor Muni Body with Cross Conveyor	SOURCEWELL PRICING		
1	Henderson	12' x 42" parallel lift plow and Flat plate hitch	SOURCEWELL PRICING		
1	Kage ind	Wing laser			
1	Pintle hitch	Pintle hitch with chipper bar			
1	Lights	Led lights strobes and work lights			
1	Force America	Force Patrol Commander Hyd system with 6100 spreader control			
1	Labor	Installation of box, plow, hitch, hydraulic kit, lighting			
		Plow lead time 150 DAYS			
		Muni Body lead time 150 Days			
Total Discount					
			Subtotal		
			Sales Tax		
			Total		

Quotation prepared by: Jordan VanDyke Owner



This is a quotation on the goods named, subject to the conditions noted below: [Describe any conditions pertaining to these prices and any additional terms of the agreement. You may want to include contingencies that will affect the quotation.]

To accept this quotation, sign here and return: _____