

## 1. Vendor Information

- Vendor Name: BILLINGS PETERBILT, INC.
- Contact Person: DAN WEIMER
- Address: 3255 N. FRONTAGE RD, BILLINGS MT, 59101
- Phone Number: 406-252-5667
- Email Address: dweimer@jgpete.com

## 2. Sourcewell Contract Information

- Sourcewell Contract Number: 032824
- Contract Expiration Date: 2028

## 3. Pricing **KOIS BROTHERS PLOW TRUCK**

- Unit Price (per truck): \$363,331.00
- Quantity: 3 Units

*Include all applicable fees (delivery, setup, etc.):*

## 4. Estimated Delivery

- Estimated Delivery Date: APRIL 2027 UPON APPROVAL IN NO LONGER THAN 2 WEEKS

## 5. Service & Support

Provide details regarding guarantees or estimated timeframes triage of trucks in terms of diagnosis and parts ordering (ex. Can diagnose and order parts within 48 hours) Provide as separate attachment.

## 6. Attachment A

- Completed Attachment A Included:  
☒ Yes ☐ No

Completed by: DAN WEIMER Date: 8-28-26

| Specification Requirement                                                                                   | Dealer Acknowledgement (Yes/No) | Please Check if Dealer installed option | Page/Section Location    |
|-------------------------------------------------------------------------------------------------------------|---------------------------------|-----------------------------------------|--------------------------|
| <b>Basic Truck Configuration</b>                                                                            |                                 |                                         |                          |
| 1. All trucks will be delivered on the same date                                                            | YES                             |                                         |                          |
| 2. Day Cab Configuration                                                                                    | YES                             |                                         | PG- 9/ 6700000           |
| 3. 48 state and Canada compliant emissions                                                                  | YES                             |                                         | PG- 5/ 2140200           |
| 4. Left hand steering                                                                                       | YES                             |                                         |                          |
| 5. Assembled in the USA                                                                                     | YES                             |                                         | DENTON, TEXAS            |
| 6. Must have local dealer support                                                                           | YES                             |                                         | BILLINGS PETERBILT, INC. |
| a. Must be within 50 miles of Yellowstone County Shop                                                       | YES                             |                                         |                          |
| 7. Will be for three (3) completely identical trucks                                                        | YES                             |                                         |                          |
| 8. Will be white in color                                                                                   | YES                             |                                         |                          |
| 9. All lighting will be LED                                                                                 | YES                             |                                         |                          |
| 10. Exhaust must exit behind and above the cab                                                              | YES                             |                                         |                          |
| 11. Gear ratios must allow truck to run at least 72mph and the rear axle ratio should be no less than 3.73  | YES                             |                                         |                          |
| 12. Hood must be assembled in such fashion to allow access if plow is installed and in the up most position | YES                             |                                         | PG- 10/ 7851100          |
| 13. Aluminum Wheels                                                                                         | YES                             |                                         | PG- 8/ 5211600,5311470   |
| <b>Engine-minimum allowable specifications</b>                                                              |                                 |                                         |                          |
| 1. 15L Cummins Engine                                                                                       | YES                             |                                         | PG- 5/ 2059213           |
| 2. Must make 550hp @ 1600rpm                                                                                | YES- 565@1900                   |                                         |                          |
| 3. 2050lb-ft @ 1250rpm                                                                                      | NO 1850 LB-FT                   |                                         | LAST PAGE EXPLANATION    |
| 4. Block heater                                                                                             | YES                             |                                         | PG- 6/ 2521090           |
| 5. Metal drain pan                                                                                          | YES                             |                                         |                          |
| 6. Magnetic drain plug                                                                                      | YES                             |                                         |                          |
| 7. Multistep engine brake                                                                                   | YES                             |                                         | PG-6/ 2812170            |
| 8. 160amp alternator                                                                                        | YES                             |                                         | PG-6/ 2513060            |
| 9. Air compressor must make at least 35 CFM at 1000 engine rpm                                              | YES                             |                                         | PG-6/ 2725270            |
| <b>Transmission</b>                                                                                         |                                 |                                         |                          |
| 1. Automatic transmission prefer Allison                                                                    | YES                             |                                         | PG-7/ 4052970            |
| a. 4500 rugged duty series                                                                                  | YES                             |                                         | PG-7/ 4052970            |
| 2. Gear selector must be mounted to the right of drivers seat on dash or column                             | YES                             |                                         | PG-7/ 4256920            |
| 3. PTO driven hydraulic pump                                                                                | YES                             |                                         |                          |
| 4. Must be able to remain activated while vehicle is in motion at highway speeds                            | YES                             |                                         |                          |
| <b>Front axle</b>                                                                                           |                                 |                                         |                          |
| 1. Tire size 425/65R22.5 Bridgestone M810 20 ply rating or equal                                            | YES                             |                                         | PG-8/ 5004060            |
| 2. 19000lbs minimum load rating                                                                             | YES                             |                                         |                          |
| 3. Heavy duty steering gear                                                                                 | YES                             |                                         | PG-3/ 1243050            |
| 4. Disc brakes                                                                                              | YES                             |                                         | PG-3/ 1354850, 1354870   |
| 5. Steel spring suspension                                                                                  | YES                             |                                         | PG-3/ 1114030            |
| 6. All moving points must be greaseable                                                                     | YES                             |                                         | PG-3/ 1380070            |
| 7. Set forward design                                                                                       | YES                             |                                         | PG-9/ 6515770            |
| <b>Rear axles</b>                                                                                           |                                 |                                         |                          |
| 1. 46,000lbs minimum load rating                                                                            | YES                             |                                         | PG-3/1526120             |
| 2. Spring style suspension                                                                                  | YES                             |                                         |                          |
| a. Henderson HMX 460                                                                                        | YES                             |                                         | PG-4/ 1824410            |
| 3. Disc brake system                                                                                        | YES                             |                                         | PG-4/ 1616305, 1616310   |
| 4. Differential lock on both axles                                                                          | YES                             |                                         | PG-4/1687090             |
| a. Dash mounted switches with indicators                                                                    | YES                             |                                         | PG-4/ 1673090            |
| b. Auto release above 25 mph                                                                                | YES                             |                                         | PARAMETER                |
| 5. Tire pressure monitoring system                                                                          | YES                             |                                         | PG-4/ 1683245            |
| 6. Rear tire size 11.00R 24.5 14 ply Bridgestone or equal                                                   | YES                             |                                         | PG-8/ 5104750            |

| Specification Requirement | Dealer Acknowledgement (Yes/No) | Please Check if Dealer Installed option | Page/Section Location |
|---------------------------|---------------------------------|-----------------------------------------|-----------------------|
|---------------------------|---------------------------------|-----------------------------------------|-----------------------|

#### Frame

|                                                     |     |  |               |
|-----------------------------------------------------|-----|--|---------------|
| 1. Will be constructed of steel                     | YES |  | PG-2/ 0514000 |
| 2. Smallest allowable will be 10.75" X 3.5" X .375" | YES |  | PG-2/ 0514000 |
| 3. Major crossmembers must be steel construction    | YES |  | PG-2/0613200  |
| 4. Single wall construction preferred               | YES |  | PG-2/ 0514000 |

#### Rear Hitch

|                                                                      |     |  |  |
|----------------------------------------------------------------------|-----|--|--|
| 1. Rated load capacity 60,000 lbs                                    | YES |  |  |
| 2. Air compensated pintle hitch                                      | YES |  |  |
| 3. Plumbed for trailer brakes                                        | YES |  |  |
| 4. Standard 7 way industrial plug for lighting                       | YES |  |  |
| 5. Standard chip spreader bar                                        | YES |  |  |
| a. 12 inch opening                                                   | YES |  |  |
| b. 1 1/4 inch diameter bar                                           | YES |  |  |
| c. 12 inches to center of bar to ground level                        | YES |  |  |
| d. Center line of bar must be at 20" +/- 1" from the rear tip of box | YES |  |  |

#### Battery

|                                                 |     |  |               |
|-------------------------------------------------|-----|--|---------------|
| 1. Externally mounted preferred if room permits | YES |  | PG-8/ 6010670 |
| 2. Battery Shutoff                              | YES |  |               |

#### Fuel tank

|                                                                       |     |  |                             |
|-----------------------------------------------------------------------|-----|--|-----------------------------|
| 1. Mounted on driver side                                             | YES |  | PG-8/ 5602135               |
| 2. 125 us gallon capacity                                             | YES |  | PG-8/ 5554340               |
| 3. Aluminum                                                           | YES |  | PG-8/ 5554340               |
| 4. External Mounted Batteries (If not tank, then else where external) | YES |  | PG-8/ 6010670               |
| 5. Heated fuel tank and fuel filter (Artic Fox and Davco 382)         | YES |  | PG-8/ 5652000 PG-8/ 2921130 |

#### DEF tank

|                           |     |  |               |
|---------------------------|-----|--|---------------|
| 1. Mounted on driver side | YES |  | PG-8/ 5652890 |
|---------------------------|-----|--|---------------|

#### Rear fender requirements

|                                                                      |     |  |              |
|----------------------------------------------------------------------|-----|--|--------------|
| 1. One set of mudflaps will be installed at rear of the drive wheels | YES |  | ON BODY      |
| 2. One set of mudflaps will be installed in front of drive wheels    | YES |  | FROM FACTORY |

#### Internal cab requirements

|                                                                                    |     |     |                        |
|------------------------------------------------------------------------------------|-----|-----|------------------------|
| 1. Vocational style cab with rear window                                           | YES |     | PG-10/ 7210540         |
| 2. Top tier HVAC system                                                            | YES |     | PG-10/ 7322010         |
| 3. Premium cab sound insulation                                                    | YES |     | PG-9/ 6540160,6540660  |
| 4. Premium instrument cluster                                                      | YES |     | PG-11/ 8070830         |
| 5. Air suspension cab                                                              | YES |     | PG-10/ 7852020         |
| 6. Driver's seat will be premium high back black or grey cloth air suspension seat | YES |     | PG-9/ 6913200          |
| a. Heavy duty seat cover included                                                  | YES | YES |                        |
| 7. 18-inch diameter driver's wheel will be fully adjustable                        | YES |     |                        |
| 8. Left- and right-hand electronic door locks                                      | YES |     | PG-10/ 7230360         |
| 9. Power Windows                                                                   | YES |     | PG-10/ 7230360         |
| 10. Power left and right hand heated mirrors                                       | YES |     | PG-10/ 7514010         |
| 11. Passenger single passenger seat                                                | YES |     | PG-9/ 6921740          |
| 12. Convex mirrors on both right and left side                                     | YES |     | PG-10/ 7514010         |
| 13. Driver and passenger side sun visors                                           | YES |     | PG-10/ TOP HIGHLIGHTED |
| 14. Standard pedal configuration                                                   | YES |     |                        |
| 15. From drivers seat full instrumentation must be visible                         | YES |     |                        |
| 16. AM/FM/Bluetooth radio                                                          | YES |     | PG-10/ 7722120         |
| 17. 40 channel CB radio factory installed                                          | YES |     | PG-10/ 7740220         |
| 18. Must be wired for additional radio to be installed by the purchasing party     | YES | YES |                        |
| a. Must have constant 20 amp power supply                                          | YES | YES |                        |

| Specification Requirement                                                          | Dealer Acknowledgement (Yes/No) | Please Check if Dealer installed option | Page/Section Location |
|------------------------------------------------------------------------------------|---------------------------------|-----------------------------------------|-----------------------|
| b. Must have ignition switched 5-amp supply                                        | YES                             | YES                                     |                       |
| c. Must be routed to a central location for mounting of additional radio           | YES                             | YES                                     |                       |
| 19. Two (2) cab top mounted LED strobe lights on each side of cab                  | YES                             |                                         | PG-12/ 8132215        |
| 20. Externally mounted grab handles on both sides of cab to assist in entering cab | YES                             |                                         | PG-10/ 7110680        |
| 21. All weather rubber style floor covering                                        | YES                             |                                         | STANDARD OPTION       |
| 22. 10 lb dry fire extinguisher mounted securely inside driver's side door         | YES                             |                                         | PG-11/ 7900320        |
| 22. Engine fresh air system must be adaptable to winter applications               | YES                             |                                         | PG-6/ 3281290         |
| a. Must be able to draw warm air from engine compartment during plowing operations | YES                             |                                         | PG6/ 3281290          |

#### Sander/ Dump Box

|                                                                  |     |  |  |
|------------------------------------------------------------------|-----|--|--|
| 1. Stainless Steel                                               | YES |  |  |
| 2. Dual Purpose 16' live bottom with bolt on conveyor covers     | YES |  |  |
| 3. 1/4" minimum floor thickness                                  | YES |  |  |
| 4. Front discharge                                               | YES |  |  |
| 5. Spinner mounted drivers side behind cab outside of frame rail | YES |  |  |
| 6. Rear facing tail and brake lights two per side                | YES |  |  |

#### Snowplow

|                                                    |            |     |  |  |
|----------------------------------------------------|------------|-----|--|--|
| 1. 12 foot straight Heinke Parallel lift plow V2.0 | HENKE PLOW | YES |  |  |
| 2. Full compression trip breakaway                 |            | YES |  |  |
| 3. Reversible                                      |            | YES |  |  |
| 4. Extendable right side with mailbox cutout       |            | YES |  |  |
| 5. 42 inch height                                  |            | YES |  |  |
| 6. Kagi inovations wingline laser plow guide       |            | YES |  |  |
| 7. Parallel lift with quick attach system          |            | YES |  |  |

#### Light Package

|                                                                 |     |  |  |
|-----------------------------------------------------------------|-----|--|--|
| 1. All Led                                                      | YES |  |  |
| 2. Two clear rear side facing at 5 and 7 positions flood lights | YES |  |  |
| 3. Two clear forward facing at 10 and 2 position flood lights   | YES |  |  |
| 4. Two per side tail light/brake light                          | YES |  |  |
| 5. Two rear facing green/yellow LED strobes                     | YES |  |  |
| 6. Two hood mounted forward facing Headlights                   | YES |  |  |
| a. Heated with high/low beam and turn signal                    | YES |  |  |

#### Air equipment

|                                                                              |     |  |               |
|------------------------------------------------------------------------------|-----|--|---------------|
| 1. Must be able to accommodate the 35 CFM requirements of the air compressor | YES |  | PG-6/ 2725270 |
| 2. Require twin air dryer setup                                              | YES |  | PG-7/ 4510340 |
| 3. Will be heated                                                            | YES |  |               |
| 4. Pull cables drains on all air tanks                                       | YES |  |               |

#### Warranty

|                                                                                                                             |     |  |  |
|-----------------------------------------------------------------------------------------------------------------------------|-----|--|--|
| 1. Factory or dealer covered warranty                                                                                       | YES |  |  |
| 2. For a term no less than 5 years or 200,000 miles from date of delivery to Yellowstone County Shop                        | YES |  |  |
| 3. Must cover engine and drive train                                                                                        | YES |  |  |
| 4. All electrical parts due to failure                                                                                      | YES |  |  |
| a. Item failure do to misuse will be excluded                                                                               | YES |  |  |
| 5. All emissions must be covered for no less than 5 years also "No exceptions"                                              | YES |  |  |
| 6. Everything installed by the manufacture or dealer prior to delivery will be covered by the warranty with said exceptions | YES |  |  |
| a. Wheels and tires                                                                                                         | YES |  |  |
| b. Brakes                                                                                                                   | YES |  |  |

| Specification Requirement                                                                                                                               | Dealer Acknowledgement (Yes/No) | Please Check if Dealer installed option | Page/Section Location |
|---------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|-----------------------------------------|-----------------------|
| c. Glass items                                                                                                                                          | YES                             |                                         |                       |
| i. Windshields                                                                                                                                          | YES                             |                                         |                       |
| ii. Back windows                                                                                                                                        | YES                             |                                         |                       |
| iii. Side windows                                                                                                                                       | YES                             |                                         |                       |
| iv. Mirrors                                                                                                                                             | YES                             |                                         |                       |
| 4. Belts                                                                                                                                                | YES                             |                                         |                       |
| 5. Hoses                                                                                                                                                | YES                             |                                         |                       |
| 7. It will be the responsibility of Yellowstone County to deliver the trucks to the dealer for repairs                                                  | YES                             |                                         |                       |
| 8. When these 3 trucks are brought in for warranty repairs, they must be diagnosed and have parts ordered within 24 hours of arrival to dealer location | YES                             |                                         |                       |
| i. This will be in writing and provided with all the documentation for the trucks                                                                       | YES                             |                                         |                       |
| 9. Must be provided with a complete parts book and shop repair manual                                                                                   | YES                             |                                         |                       |
| i. Can be printed or digital                                                                                                                            | YES                             |                                         |                       |
| ii. Can be online accessible for a period of 10 years                                                                                                   | YES                             |                                         |                       |

Explanation on the engine section for the 2050 lb torque that i had to put a "NO" on- Allison does not allow any of their transmissions to be installed behind a motor of any brand with 2050 torque rating. In thier brochure they point out it will take that torque, but they do not allow any manufacture to install it in their chassis with a 2050 torque rating.



## BILLINGS PETERBILT, INC.

3255 N FRONTAGE ROAD • BILLINGS, MT 59101 • PHONE (800) 548-7565

STOCK #  
TBD

DATE:  
8/28/2026

### VEHICLE BUYER'S ORDER AND PURCHASE AGREEMENT

|                                    |      |           |       |                      |  |                         |  |
|------------------------------------|------|-----------|-------|----------------------|--|-------------------------|--|
| PURCHASER'S NAME                   |      |           |       | RES OR BUS PHONE     |  | CELL PHONE              |  |
| YELLOWSTONE COUNTY ROAD AND BRIDGE |      |           |       |                      |  |                         |  |
| ADDRESS                            |      |           |       | CITY                 |  | STATE                   |  |
| 3321 KING AVE E                    |      |           |       | BILLINGS             |  | MT                      |  |
|                                    |      |           |       | VIN/Quote #          |  | ZIP                     |  |
|                                    |      |           |       | TBD                  |  | 59101                   |  |
| NEW/USED                           | YEAR | MAKE      | MODEL |                      |  | COLOR                   |  |
| NEW                                | 2027 | PETERBILT | 567   |                      |  | WHITE                   |  |
|                                    |      |           |       | TRADE INFORMATION    |  | RETAIL PRICE W/ OPTIONS |  |
|                                    |      |           |       | YEAR                 |  | 362,331.00              |  |
|                                    |      |           |       | BODY                 |  |                         |  |
| 2027 PETERBILT WITH KOIS BROTHERS  |      |           |       | MAKE                 |  | FET                     |  |
| PLOW SYSTEM                        |      |           |       | MODEL                |  | EXTENDED WARRANTY       |  |
|                                    |      |           |       | COLOR                |  |                         |  |
| AS REQUESTED BY BID SPEC WITH      |      |           |       | MILEAGE              |  | SUBTOTAL                |  |
| ALL WARRANTIES                     |      |           |       | -                    |  | 362,331.00              |  |
|                                    |      |           |       | SLEEPER              |  | STATE TIRE TAX          |  |
|                                    |      |           |       | ENGINE               |  | STATE SALES TAX         |  |
|                                    |      |           |       |                      |  | LICENSE & REGISTRATION  |  |
|                                    |      |           |       | TRADE PAYOFF TO WHOM |  | DOC FEE                 |  |
|                                    |      |           |       |                      |  | 295.00                  |  |
|                                    |      |           |       |                      |  | TOTAL                   |  |
|                                    |      |           |       |                      |  | 362,626.00              |  |
|                                    |      |           |       |                      |  | TRADE ALLOWANCE         |  |
|                                    |      |           |       |                      |  | PAYOFF                  |  |
|                                    |      |           |       | PHONE #              |  | EQUITY                  |  |
|                                    |      |           |       | ACCT #               |  | QUANTITY                |  |
|                                    |      |           |       | PAYOFF               |  | 1                       |  |
|                                    |      |           |       | DEPOSIT              |  |                         |  |
|                                    |      |           |       | GOOD UNTIL           |  | DOWN PAYMENT            |  |
|                                    |      |           |       |                      |  | BALANCE DUE             |  |
|                                    |      |           |       |                      |  | 362,626.00              |  |

|                       |      |                                                                                                                            |
|-----------------------|------|----------------------------------------------------------------------------------------------------------------------------|
|                       | \$ - | <b>Purchaser agrees to be responsible for any manufacturing surcharges applied after the order date (see item 7 below)</b> |
|                       | \$ - |                                                                                                                            |
|                       | \$ - |                                                                                                                            |
|                       | \$ - |                                                                                                                            |
|                       | \$ - | <b>ALL VEHICLES ARE SOLD "AS IS" UNLESS OTHERWISE INDICATED HERE X</b>                                                     |
|                       | \$ - |                                                                                                                            |
|                       | \$ - |                                                                                                                            |
|                       | \$ - |                                                                                                                            |
| <b>TOTAL WARRANTY</b> | \$ - |                                                                                                                            |

NO VERBAL ORDERS-THIS IS COMPLETE AGREEMENT

PURCHASER'S SIGNATURE

DATE

NOT VALID UNLESS ACCEPTED BY MANAGEMENT

VERSION CONTROL: 2/1/2025

DEALER OR HIS AUTHORIZED REPRESENTATIVE

NOT VALID UNLESS ACCEPTED BY MANAGEMENT

**-General Terms and Conditions-**

The Purchaser and Dealer further understand and agree that, coupled with terms and conditions provided on page 1, the following terms and conditions govern the subject matter of this Vehicle Buyer's Order and Purchase Agreement (hereinafter "Agreement"):

1. Purchaser agrees to purchase the vehicle(s) listed on the front page of this Agreement within five (5) days of signing this Agreement or in the case of special ordered vehicle(s) (defined in paragraph 2), within five(5) days of receipt of said vehicle(s) by Dealer. This Agreement is non-cancellable for any reason.
2. Any vehicle(s) not in the Dealer's inventory as of the date of this Agreement are defined herein as special ordered vehicles and are referred to herein as SOV(s). SOV(s) are non-cancelable for any reason. SOV(s) also include all hybrid and electric vehicle(s).
3. Purchaser shall deliver the original bill of sale and the title to any used vehicle traded herein along with the delivery of such vehicle in the same condition containing the same equipment as when appraised, reasonable wear and tear excepted, and the Purchaser warrants such vehicle to be his property free and clear of lien and encumbrances except as otherwise disclosed to Dealer on the front page hereof. If no trade is listed on the front page of this Agreement, then no trade will be accepted by Dealer.
4. The failure or refusal of the Purchaser to complete the purchase contemplated herein shall be a material breach of this Agreement and Dealer shall be entitled to all rights and remedies under the law, including, but not limited to, lost profits, damages, specific performance and its attorney fees and court costs. The Purchaser agrees, that in addition to any other legal remedy available to Dealer, any deposit provided to Dealer shall be retained and forfeited to Dealer, and/or in the event a used vehicle has been taken in trade, the Dealer may sell said used vehicle, and the Dealer shall be entitled to reimburse itself out of the proceeds of such sale, to cover its expense and losses incurred or suffered as the result of Purchaser's failure to complete said purchase.
5. The manufacturer has the right to make changes in the model or design of any accessories and part of any new motor vehicle at any time without creating an obligation on the part of either the Dealer or the manufacturer to make corresponding changes in the vehicle covered by this Agreement either before or subsequent to the delivery of such vehicle to the Purchaser. Purchaser agrees to accept the vehicle as manufactured and delivered, even if specific parts or components are not installed or not available at delivery.
6. In no event, shall Dealer be liable for delays or failure to deliver the vehicle on a specified day, including delays caused by the manufacturer, accidents, sureties, fires or other causes or acts beyond the control of the Dealer. Any delays caused by pandemics, war, shortages, civil unrest or similar circumstance are at Purchaser's risk.
7. From time-to-time manufacturer surcharges are added to the vehicle(s) listed on the front page of this Agreement. Purchaser agrees to be responsible for any such surcharges at the time of delivery. Surcharges amounts will be added to the final invoice and documentation supporting surcharges will be provided to the Purchaser.
8. NO WARRANTIES EXPRESSED OR IMPLIED, ARE MADE OR WILL BE DEEMED TO HAVE BEEN MADE BY EITHER THE DEALER OR THE MANUFACTURER OF A MOTOR VEHICLE OR MOTOR VEHICLE CHASSIS PURCHASED HEREUNDER, vehicle on a specified day, including delays A COPY OF WHICH WILL BE DELIVERED TO PURCHASER. AT THE TIME OF DELIVERY OF A MOTOR VEHICLE OR MOTOR VEHICLE CHASSIS, SUCH WARRANTY SHALL BE EXPRESSLY IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND THE REMEDIES SET FORTH IN SUCH WARRANTY WILL BE THE ONLY REMEDIES AVAILABLE TO ANY PERSON WITH RESPECT TO SUCH MOTOR VEHICLE OR MOTOR VEHICLE CHASSIS.  
NO WARRANTIES, EXPRESS OR IMPLIED, ARE MADE BY THE DEALER WITH RESPECT TO USED MOTOR VEHICLES OR MOTOR VEHICLE CHASSIS FURNISHED HEREUNDER EXCEPT AS MAY BE EXPRESSED IN WRITING BY THE DEALER FOR SUCH USED MOTOR VEHICLE OR MOTOR VEHICLE CHASSIS, WHICH WARRANTY, IF SO EXPRESSED IN WRITING.
9. In case the vehicle covered by this agreement is a used or demonstrator vehicle, no warranty or representation is made as to how such vehicle has been used, regardless of the mileage shown on the speedometer of said used vehicle.
10. In the event that it becomes necessary for the Dealer to enforce any of the terms and conditions of the agreement, Purchaser agrees to pay reasonable attorney's fees and court costs, including collections costs.
11. All past due amounts and payments due to Dealer hereunder shall bear interest at the rate of eighteen (18%) percent per annum.
12. This agreement is non-transferable by the Purchaser nor may any of Purchaser's rights or obligations hereunder be assigned. Dealer may assign all of its rights and obligations hereunder, including to its Affiliates, upon reasonable notice to Purchaser.
13. LIABILITY INSURANCE COVERAGE FOR BODILY AND DAMAGE CAUSED TO OTHERS IS NOT INCLUDED IN THIS AGREEMENT.
14. PURCHASER REPRESENTS that he/she is 18 years of age or older at the time of the consummation of the purchase hereunder. Purchaser further represents that if it is ordering electric vehicle(s) it has the ability to charge said vehicle(s) and is not relying on Dealer to provide charging services.
15. Title/MSO to the vehicle shall remain with the Dealer until purchase price is paid in full; and, until such payment is paid in full, Purchaser hereby grants to Dealer a security interest in the subject vehicle for the purpose of securing payment therefore.
16. No agreement, verbal or otherwise, not contained in this agreement will be recognized.
17. In case of the vehicle covered by this agreement is a used vehicle, the information you see on the window form (Buyer's Guide) for this vehicle shall be made part of this Agreement. Provided, any terms or conditions on such window form which conflict with the terms and conditions of this Agreement, shall govern.
18. The parties agree the term "DEPOSIT" (as used herein) means any deposit paid by the Purchaser to secure, order, or hold Vehicle(s) from Dealer, or its Affiliates. Deposit made by Purchaser is non-refundable.
19. Federal Excise Tax will be remitted on the vehicle(s) listed on the front page of this agreement. Purchaser agrees any additions added to the vehicle(s) and not listed on the front page of this agreement which are subject to said tax will be reported to and paid directly by the Purchaser to the Internal Revenue Service.
20. Purchaser is solely responsible to conduct its own due diligence when determining engine size, torque ratings, tires and wheel size, and all other specifications necessary for the proper use of any motor vehicle. Purchaser is solely responsible to ensure any changes made by the manufacturer to the vehicle in the build process conforms to its uses, needs, and requirements. Dealer is not responsible for any changes between orders submitted to the manufacturer and vehicles delivered by the manufacturer. Purchaser is solely responsible for understanding emission requirements and the states' laws where it intends to operate any Vehicle(s) purchased from Dealer. Purchaser is not relying on any recommendations by Dealer as to the legality of operating any Vehicle(s) in any country, state, city or location.
21. Purchaser acknowledges, understands, and agrees that Dealer may commingle the deposit with Dealer's other funds, and that neither Dealer nor its Affiliates shall be required to place the deposit in a trust account or to pay Purchaser interest thereon.
22. For the purposes of this Agreement and all attendant documents, "Affiliates" shall mean any individual, joint venture, partnership, corporation, business entity, member or stockholder which controls, is controlled by, or is under common control with, or the management and operations of which are substantially influenced by, Dealer.
23. This Agreement is the exclusive agreement between the parties with respect to its subject matter and as of its reference date supersedes all prior agreements, negotiations, representations, and proposals, written or oral, related to its subject matter. Its terms cannot be modified, supplemented or rescinded except by an agreement in writing signed by an authorized representative of all parties. There are no conditions precedent to the effectiveness of this Agreement other than those expressly stated in this Agreement. In entering into this Agreement, neither party has relied upon any statement, representation, warranty or agreement of the other party except for those expressly contained in this Agreement.
24. In the event that any portion of this Agreement shall be held to be unenforceable, the remaining portions of this Agreement shall remain in full force and effect.
25. Except as otherwise provided in this document, this Agreement may be modified, superseded, or voided only upon the written and signed agreement of the parties.
26. This Agreement and any disputes arising out of or in connection with this Agreement shall be governed by and construed in accordance with the laws of the State of Utah except for that portion relating to conflicts of laws. Any matter involving interpretation or enforcement of this Agreement shall be brought in the state or federal courts in Salt Lake County, Utah. The parties hereby accept the jurisdiction of those courts.
27. The Dealer does not have control of additional surcharges added by the manufacturer after the order date. Any such surcharges will be passed on to the Purchaser, and documentation supporting those surcharges will be provided to the Purchaser.

(Rev. 11-30-2023)

VIN #

Make Checks Payable to BILLINGS PETERBILT, INC.

Deposit Amount: \$

Customer Company Name

BILLINGS PETERBILT, INC.

Signature

Signature

Date

Date

VERSION CONTROL: 2/1/2025



Jackson Group Peterbilt – Billings (M550)  
3255 N. Frontage Road  
Billings, Montana 59101

YELLOWSTONE COUNTY ROAD & BRI  
3321 KING AVE E  
BILLINGS, Montana 59101  
United States of America

Dan Weimer  
Cell Phone:  
Office Phone: 406-252-5667  
Email: dweimer@jgpete.com

GREG FISHER

## Vehicle Summary

| Unit                    |                 | Chassis                    |       |
|-------------------------|-----------------|----------------------------|-------|
| Model:                  | Model 567       | Fr Axle Load (lbs):        | 20000 |
| Type:                   | Full Truck      | Rr Axle Load (lbs):        | 46000 |
| Description 1:          | PLOW TRUCKS     | G.V.W.R. (lbs):            | 66000 |
| Description 2:          |                 | G.C.W. (lbs):              | 66000 |
| Application             |                 | Road Conditions:           |       |
| Intended Serv.:         | Snowplow        | Class A (Highway)          | 95    |
| Commodity:              | Other Commodity | Class B (Hwy/Mtn)          | 5     |
|                         |                 | Class C (Off-Hwy)          | 0     |
|                         |                 | Class D (Off-Road)         | 0     |
| Body                    |                 |                            |       |
| Type:                   | End Dump        | Maximum Grade:             | 6     |
| Length (ft):            | 16              | Wheelbase (in):            | 220   |
| Height (ft):            | 13              | Overhang (in):             | 55    |
| Max Laden Weight (lbs): | 8500            | Fr Axle to BOC (in):       | 90.1  |
| Trailer                 |                 |                            |       |
| No. of Trailer Axles:   | 0               | Cab to Axle (in):          | 129.9 |
| Type:                   |                 | Cab to EOF (in):           | 184.9 |
| Length (ft):            | 0               | Overall Comb. Length (in): | 306   |
| Height (ft):            | 0               | Special Req.               |       |
| Kingpin Inset (in):     | 0               |                            |       |
| Corner Radius (in):     | 0               |                            |       |
| Restrictions            |                 |                            |       |
| Length (ft):            | 40              |                            |       |
| Width (in):             | 102             |                            |       |
| Height (ft):            | 13.5            |                            |       |

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

Note: All sales are F.O.B. designated plant of manufacture.



| Sales Code                   | Std/ Opt | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | \$ List | Weight |
|------------------------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|--------|
| <b>Base Model</b>            |          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |         |        |
| 0005671                      | S        | <b>Model 567</b><br>The Model 567 is available in both a set-forward and set-back front axle configuration to provide customers with maximum versatility for their application requirements. For weight-sensitive applications, the set-forward front axle provides optimized weight distribution and compliance with bridge laws. The Model 567 has steer axle ratings up to 22,000 lbs. The 567 also offers single, tandem or tridem drive axles and a variety of lift axles for added versatility. Available with a 115" or 121" BBC and as a day cab or with a selection of detachable sleeper configurations, the 567 is as versatile as it is reliable. | 214,213 | 14,800 |
| 0091200                      | S        | <b>Other Commodity</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 0       | 0      |
| 0093150                      | O        | <b>Snowplow</b><br>Truck which is configured for mounting a snowplow to the front. May also have dump or other body.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 0       | 0      |
| 0095170                      | O        | <b>End Dump</b><br>Do not use for side dump bodies                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 0       | 0      |
| 0098170                      | S        | <b>United States Registry</b><br>Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.                                                                                                                                                                                                                                                                                                                                                                                                                                                | 0       | 0      |
| <b>Configuration</b>         |          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |         |        |
| 0200700                      | S        | <b>Not Applicable</b><br>Secondary Manufacturer                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 0       | 0      |
| <b>Frame &amp; Equipment</b> |          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |         |        |
| 0514000                      | O        | <b>10-3/4" Steel Rails To 354"</b><br>10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 526     | 260    |
| 0611250                      | O        | <b>Heavy-Duty Iron Front Spring Brackets</b><br>With Front Air Leaf the front spring bracket is iron but not the shackle bracket                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 493     | 35     |
| 0611330                      | O        | <b>Zinc Coated Anti Corrosion Treated Frame Rails</b><br>Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common.                                                                                                                                                                                                                                                                                                                                                                  | 387     | 4      |
| 0613200                      | O        | <b>5-Pc Crossmembers, BOC Excludes Suspension</b><br>Steel crossmember with aluminum gussets                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 743     | 14     |
| 0620571                      | O        | <b>Front Frame Hard Point Structure for Equipment Mounting 2.1M HD</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 2,827   | 551    |
| 0620572                      | O        | <b>Del PB Installed Kicker Brace For Front Frame Hard Point Structure</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | -264    | 0      |
| 0644090                      | O        | <b>EOF Square without Crossmember</b><br>End-of-frame square without crossmember. For use with body builder installed crossmember.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 60      | -64    |
| 0651090                      | O        | <b>Omit Rear Mudflaps and Hangers</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | -58     | -25    |

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|------------|----------|-------------|---------|--------|
|------------|----------|-------------|---------|--------|

### Front Axle & Equipment

|         |   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |       |      |
|---------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|------|
| 1011890 | O | <b>PACCAR FX-20 Steer Axle 20,000 lbs. 4" Drop</b><br>Axle is designed for applications with a gross axle weight rating (GAWR) of 20,000 pounds. Front axle is designed for demanding applications such as construction, heavy haul, refuse, and other vocational uses. Robust forged steel beam construction for long-lasting performance. It utilizes innovative tapered kingpin roller bearings for more efficient operation and improved steering efficiency.<br><br>The PACCAR Steer Axle comes standard with the PACCAR warranty of 5 years, 750,000 miles. | 2,863 | 137  |
| 1114030 | O | <b>Taper Leaf Springs, Shocks 20,000 lb</b><br>Standard with Heavy Resistance Shocks.                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 741   | -156 |
| 1243050 | O | <b>Power Steering Sheppard HD94 Dual Gear</b><br>For use with 16,000 to 20,000 lb. axle ratings.                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 2,079 | 100  |
| 1250250 | O | <b>Power Steering Reservoir Frame Mounted w/Cooler</b><br>A power steering cooler helps reduce the heat of the power steering fluid. This is commonly used with systems that may experience more stress from towing or off-road driving.                                                                                                                                                                                                                                                                                                                          | 195   | 2    |
| 1354850 | O | <b>PHP10 Iron PreSet PLUS Hubs - Air Disc</b><br>Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still offering dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear.                                                                                                                                                   | -65   | 42   |
| 1354870 | O | <b>Severe Service Disc Brake Rotor - Steer Axle</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 360   | 97   |
| 1380070 | O | <b>Greasable Front Spring Pins</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 67    | 0    |
| 1380380 | S | <b>Tenneco Shocks For Steer Axle</b><br>Integrated front suspension to suit heavy duty truck market, combining the air spring and the damper into one module.                                                                                                                                                                                                                                                                                                                                                                                                     | 0     | 0    |
| 1380490 | O | <b>PACCAR FX Wide Track IPO Standard</b><br>71in KPI IPO 69in front axle for improved turning radius.                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 0     | 15   |
| 1391480 | O | <b>Pad Dust Shields for Air Disc Brakes; Front Axle</b><br>Pad dust shields for air disc brakes can increase brake life. Brake dust shields reduce the buildup of road grime, extend brake system life and prevent premature failure.                                                                                                                                                                                                                                                                                                                             | 51    | 2    |
| 1392180 | O | <b>Meritor EX+L Optimized Linehaul Air Disc Brakes</b><br>Steer Axle. Meritor EX+L Optimized Air Disc Brakes with calipers that are 11 to 15 pounds lighter, per wheel end, than current EX+L brake calipers.                                                                                                                                                                                                                                                                                                                                                     | 68    | 0    |

### Rear Axle & Equipment

|         |   |                                                                                                                                                                                                                                                                                                                                                                                                |       |     |
|---------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-----|
| 1526120 | O | <b>Meritor RT46-160 46,000 lb</b><br>Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD FE 75W-90 synthetic axle lube | 5,163 | 634 |
|---------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-----|

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



| Sales Code | Std/ Opt | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | \$ List | Weight |
|------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|--------|
|            |          | provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life. If code 1526120 (RT46-160) is ordered with 1680460 (Heavy Wall), you will get the 16 mm wall, but not the improved carrier that is in 1526130 code (RT46-160E) that also has a 16 mm wall. This could affect Heavy Haul service warranty length in Canada per Meritor. |         |        |
| 1616305    | O        | <b>PHP10 Iron Preset + Hubs - Air Disc</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 1,715   | 0      |
| 1616310    | O        | <b>Severe Service Disc Brake Rotor - Drive</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | -124    | 14     |
| 1660040    | O        | <b>Pad Dust Shields for Air Disc Brakes, Drive Axle(s)</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 44      | 0      |
| 1673090    | O        | <b>Separate Dash Controls, Cont Trac Full Lock</b><br>Dana Spicer or Meritor - Tandem or Tri-Drive Axles                                                                                                                                                                                                                                                                                                                                                                                                                                              | 121     | 2      |
| 1680500    | O        | <b>SBM Valve</b><br>Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.                                                                                                                                                                                                                    | 277     | 0      |
| 1680525    | O        | <b>Pneumatic Park Brake</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 0       | 0      |
| 1680950    | O        | <b>Stability System Not Selected Or Not Available</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | -6      | 0      |
| 1682710    | S        | <b>Anti-Lock Braking System (ABS) 6S6M</b><br>ABS-6. Includes air braking system.                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 0       | 0      |
| 1683245    | S        | <b>Tire Pressure Monitoring System</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 0       | 0      |
| 1684200    | S        | <b>Synthetic Axle Lubricant All Axles</b><br>Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.                                                                     | 0       | 0      |
| 1687090    | O        | <b>Diff Lock Tandem Axles</b><br>With Speed Interlock. Automatically Disengages Wheel Diff Lock at Speeds Above 25 mph.                                                                                                                                                                                                                                                                                                                                                                                                                               | 2,004   | 60     |
| 1687175    | O        | <b>Meritor EX+L Optimized Air Disc Brakes</b><br>Tandem Drive. Meritor EX+L Optimized Air Disc Brakes with calipers that are 11 to 15 pounds lighter, per wheel end, than current EX+L brake calipers.                                                                                                                                                                                                                                                                                                                                                | -26     | 0      |
| 1703730    | O        | <b>Ratio 3.73 Rear Axle</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 0       | 0      |
| 1824410    | O        | <b>Hendrickson HMX EX 460 46,000 LBS., 54"</b><br>Haulmaax, 70K Creep Rating. Includes Traax Rod as standard, option 1920905 is not needed or available. Progressive load spring system easily adjusts to the load for an enhanced combination of empty-ride quality and loaded stability.                                                                                                                                                                                                                                                            | 3,585   | 184    |

## Engine & Equipment

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



| Sales Code | Std/ Opt | Description                                                                                                                                                                                                                                  | \$ List | Weight |
|------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|--------|
| 2059213    | O        | <b>X15 565@1900 GOV@1900 1850@1000</b><br>Performance Series (2024 Emissions)                                                                                                                                                                | 16,695  | 428    |
|            |          | N21350 C121 68....Maximum Accelerator Vehicle                                                                                                                                                                                                |         |        |
|            |          | N21370 C128 68....Maximum Cruise Control Speed                                                                                                                                                                                               |         |        |
|            |          | N21460 C132 1400...PTO Maximum Engine Speed                                                                                                                                                                                                  |         |        |
|            |          | N21520 C133 5.....Idle Shutdown Timer                                                                                                                                                                                                        |         |        |
|            |          | N21610 C188 39....Idle Shutdown Cold Ambient A                                                                                                                                                                                               |         |        |
|            |          | N21620 C189 60....Idle Shutdown Intermediate A                                                                                                                                                                                               |         |        |
|            |          | N21630 C190 80....Idle Shutdown Hot Ambient Ai                                                                                                                                                                                               |         |        |
|            |          | N21550 C206 35....Idle Shutdown Percent Engine                                                                                                                                                                                               |         |        |
|            |          | N21340 C209 100...Maximum Vehicle Speed                                                                                                                                                                                                      |         |        |
|            |          | N21510 C225 YES...Idle Shutdown with Parking B                                                                                                                                                                                               |         |        |
|            |          | N21450 C231 NO....Gear Down Protection                                                                                                                                                                                                       |         |        |
|            |          | N21570 C233 NO....Idle Shutdown Manual Overrid                                                                                                                                                                                               |         |        |
|            |          | N21440 C234 NO....Engine Protection Shutdown                                                                                                                                                                                                 |         |        |
|            |          | N21480 C238 NO....Cruise Control and Engine Br                                                                                                                                                                                               |         |        |
|            |          | N21470 C239 NO....Cruise Control Auto-Resume                                                                                                                                                                                                 |         |        |
|            |          | N21430 C333 0.....Driver Initiated OverrideMax                                                                                                                                                                                               |         |        |
|            |          | N21410 C334 0.....Driver Initiated Override Ma                                                                                                                                                                                               |         |        |
|            |          | N21590 C382 YES...Idle Shutdown Hot Ambient Au                                                                                                                                                                                               |         |        |
|            |          | N21500 C395 0.....Green House Gas Automatic En                                                                                                                                                                                               |         |        |
|            |          | N21530 C396 YES...Idle Shutdown Warning Period                                                                                                                                                                                               |         |        |
|            |          | N21540 C397 60....Idle Shutdown Warning Period                                                                                                                                                                                               |         |        |
|            |          | N21320 C399 100...Green House Gas Vehicle Spee                                                                                                                                                                                               |         |        |
|            |          | N21400 C400 252...Driver Initiated Override Re                                                                                                                                                                                               |         |        |
|            |          | N21420 C401 10....Green House Gas Vehicle Spee                                                                                                                                                                                               |         |        |
|            |          | N21330 C402 0.....Green House Gas Vehicle Spee                                                                                                                                                                                               |         |        |
| 2091120    | S        | <b>EMUX Electronics Architecture</b>                                                                                                                                                                                                         | 0       | 0      |
| 2091305    | S        | <b>Engine Idle Shutdown Timer Enabled</b>                                                                                                                                                                                                    | 0       | 0      |
| 2091315    | O        | <b>Enable EIST Ambient Temp Overrule</b>                                                                                                                                                                                                     | 0       | 0      |
| 2091372    |          | <b>Eff EIST NA Expiration Miles</b>                                                                                                                                                                                                          | 0       | 0      |
| 2091640    |          | <b>Effective VSL Setting NA</b>                                                                                                                                                                                                              | 0       | 0      |
| 2092015    | O        | <b>Typical Operating Speed 70 MPH</b>                                                                                                                                                                                                        | 0       | 0      |
| 2092033    | S        | <b>Powertrain Optimized for Balance</b><br>Best analysis for vehicles where service includes frequent start and stop cycles.                                                                                                                 | 0       | 0      |
| 2120160    | O        | <b>TRV For DAVCO Only</b><br>X15 and P-10                                                                                                                                                                                                    | 48      | 0      |
| 2140200    | O        | <b>CARB Engine Idling Compliance</b><br>PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard. | 0       | 0      |
| 2140410    | S        | <b>Engine Brake Controls Located on RH Column</b>                                                                                                                                                                                            | 0       | 0      |
| 2140450    | O        | <b>Remote PTO/Throttle, 12-Pin</b><br>Eng Bay Remote Control Provision                                                                                                                                                                       | 135     | 0      |
| 2140660    | O        | <b>CARB Emission Compliant Engine</b>                                                                                                                                                                                                        | 0       | 0      |
| 2140700    | S        | <b>EPA Engine Idling Compliance</b>                                                                                                                                                                                                          | 0       | 0      |

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



| Sales Code | Std/ Opt | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | \$ List | Weight |
|------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|--------|
| 2513060    | S        | <b>PACCAR 160 Amp Alternator, Brushed</b><br>PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 0       | 0      |
| 2521090    | S        | <b>Immersion Type Block Heater 110-120V</b><br>Standard location is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.                                                                                                                                                                                                                                                                                                                                                                               | 0       | 0      |
| 2522090    | O        | <b>PACCAR Premium Starter - X15 Engines Only</b><br>PACCAR Premium 12 volt. Better cranking power, lower current draw and improved warranty to 36 months / 350,000 mi / 560,000 km.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 462     | 0      |
| 2538040    | S        | <b>3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA</b><br>Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 0       | 0      |
| 2539716    | O        | <b>CAB &amp; SLPR POWER DISC SW MTD ON BBOX</b><br>(KISSLING DISC SW 300A)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 643     | 3      |
| 2539720    | S        | <b>Low Voltage Disconnect System</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 0       | 0      |
| 2621000    | O        | <b>2-Speed Fan Clutch For Frequent Start/Stops</b><br>A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.                                                                                                                                                                                                                                                                                                                                       | 506     | 0      |
| 2725270    | O        | <b>37.4 CFM Air Compressor</b><br>X15                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 275     | 27     |
| 2812170    | O        | <b>Jacobs Compression Brake ISX/ISX15/X15</b><br>Features a dedicated cam lobe design for optimum power and three-stage engine brake operation.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 0       | 0      |
| 2921130    | O        | <b>DAVCO 382 Fuel/Water Separator</b><br>The Fuel Pro 382 is a combination of diesel fuel filtration and water separator that is recommended for heavy-duty diesel engines with flow rates up to 180 gallon/hour.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 498     | 0      |
| 2921340    | O        | <b>12V and 120V Heat for Fuel Filter</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 238     | 3      |
| 3114270    | S        | <b>High Efficiency Cooling System</b><br>Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 520 1242 sq in, 579 1325 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 567 1440 sq in, 589 1604 sq in. | 0       | 0      |
| 3281290    | O        | <b>Inside/Outside Air Intake</b><br>Cab mounted controls                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 1,044   | 10     |
| 3291680    | S        | <b>(1) Air Cleaner Firewall Mounted</b><br>Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 0       | 0      |

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



| Sales Code | Std/ Opt | Description                                                          | \$ List | Weight |
|------------|----------|----------------------------------------------------------------------|---------|--------|
| 3367160    | S        | Exhaust Single RH Side of Cab<br>DPF/SCR RH Under Cab, Single Module | 0       | 0      |
| 3381770    | O        | Curved Tip Standpipe(s)                                              | 43      | 1      |
| 3387870    | S        | 24" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)                       | 0       | 0      |

### Transmission & Equipment

|         |   |                                                                                                                                                                                                                                                         |        |     |
|---------|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|-----|
| 4052970 | O | Allison 4500 RDS-P Transmission, Gen 6<br>Rugged Duty Series                                                                                                                                                                                            | 29,199 | 528 |
| 4211520 | O | SPL250 Lite HT Driveline, 1 Midship Bearing                                                                                                                                                                                                             | 1,562  | 85  |
| 4216330 | O | SPL170 XL Driveline Interaxle<br>Dana Spicer Life Series heavy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles.                                                                                                   | 802    | 5   |
| 4250900 | O | Main Transmission Rear Support<br>Additional rear support for the transmission to provide a firm, durable design that improves stabilization of the drivetrain in rugged terrain                                                                        | 124    | 11  |
| 4252890 | O | Allison FuelSense Not Desired<br>Dynamic Shift Sensing                                                                                                                                                                                                  | 0      | 0   |
| 4252940 | O | Allison Neutral At Stop<br>Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max packages only. | 0      | 0   |
| 4256740 | O | Allison 6-Speed Configuration, Wide Ratio Gears<br>Allison 4500 transmission only                                                                                                                                                                       | 0      | 0   |
| 4256920 | O | Dash Mounted Push Button Shifter<br>Available with Allison transmissions                                                                                                                                                                                | 281    | 0   |

### Air & Trailer Equipment

|         |   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |       |    |
|---------|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|----|
| 4510340 | O | (2) Bendix AD-IS Air Dryers, Everflow Switching<br>Module, coalescing filters                                                                                                                                                                                                                                                                                                                                                                                                   | 1,773 | 34 |
| 4520420 | O | Pull Cords All Air Tanks                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 2     | 1  |
| 4540420 | S | Nylon Chassis Hose                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 0     | 0  |
| 4543320 | S | Steel Painted Air Tanks<br>All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed. | 0     | 0  |
| 4610890 | O | Body Lighting Junction Box, With Wiring<br>Located end-of-frame                                                                                                                                                                                                                                                                                                                                                                                                                 | 283   | 0  |
| 4610920 | S | Self-Returning Brake Hand Valve<br>Dash mounted controls                                                                                                                                                                                                                                                                                                                                                                                                                        | 0     | 0  |
| 4612780 | O | AE Connection EOF, 7-Way Socket, 4' Additional<br>Lines coiled and strapped to frame, without gladhands                                                                                                                                                                                                                                                                                                                                                                         | -138  | 15 |
| 4615250 | O | Fitting For F/O Air Port                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 65    | 0  |

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



| Sales Code                      | Std/ Opt | Description                                                                                                                                                                                                                                                                                                                                                                      | \$ List | Weight |
|---------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|--------|
|                                 |          | The furnished by owner fitting air port is mounted outboard of the driver's seat. This allows operators access to pressurize truck air, to maintain clean air in the cab.                                                                                                                                                                                                        |         |        |
| <b>Tires &amp; Wheels</b>       |          |                                                                                                                                                                                                                                                                                                                                                                                  |         |        |
| 5004060                         | O        | <b>FF: CN 20ply 425/65R22.5 HAC3</b><br>Efficiency Rating: Optimal<br>Wide base, all-position fitment for on/off, mixed service applications.<br>Includes TPMS sensor.                                                                                                                                                                                                           | 1,330   | 146    |
| 5104750                         | O        | <b>RR: CN 16Ply 11R24.5 Conti HDR2+</b>                                                                                                                                                                                                                                                                                                                                          | 1,452   | 168    |
| 5190008                         | S        | <b>Code-rear Tire Qty 08</b>                                                                                                                                                                                                                                                                                                                                                     | 0       | 0      |
| 5211600                         | O        | <b>FF: Accur 29683SP 22.5X12.25 Alm</b><br>Std Polish, 2.88" Inset                                                                                                                                                                                                                                                                                                               | 1,073   | -10    |
| 5311470                         | O        | <b>RR: Accuride 42362SP 24.5X8.25 Aluminum Wheel</b><br>Standard polish.                                                                                                                                                                                                                                                                                                         | 2,184   | -136   |
| 5390008                         | S        | <b>Code-rear Rim Qty 08</b>                                                                                                                                                                                                                                                                                                                                                      | 0       | 0      |
| <b>Fuel Tanks</b>               |          |                                                                                                                                                                                                                                                                                                                                                                                  |         |        |
| 5554340                         | O        | <b>26" Aluminum 135 Gallon Fuel Tank LH U/C</b><br>Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks. | 862     | 42     |
| 5602135                         | O        | <b>Location LH U/C 135 Gallon</b>                                                                                                                                                                                                                                                                                                                                                | 0       | 0      |
| 5650490                         | O        | <b>Fuel Cooler</b><br>Required with single fuel tank                                                                                                                                                                                                                                                                                                                             | 193     | 15     |
| 5652000                         | O        | <b>(1) C450 Fuel Heater, (1) Tank</b><br>Integral fuel pick-up tube                                                                                                                                                                                                                                                                                                              | 1,163   | 29     |
| 5652340                         | O        | <b>Heavy-Duty Fuel Tank Step Reinforcements</b>                                                                                                                                                                                                                                                                                                                                  | 312     | 5      |
| 5652890                         | S        | <b>DEF Tank Mounted LH BOC</b><br>Models 220 and 520 mounted left hand back-of-cab.                                                                                                                                                                                                                                                                                              | 0       | 0      |
| 5652980                         | S        | <b>DEF To Fuel Ratio Between 1:1 And 2:1</b>                                                                                                                                                                                                                                                                                                                                     | 0       | 0      |
| 5655019                         | S        | <b>DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal</b>                                                                                                                                                                                                                                                                                                                                 | 0       | 0      |
| 5760010                         | O        | <b>RH Tank None Furnished</b>                                                                                                                                                                                                                                                                                                                                                    | -714    | -86    |
| <b>Battery Box &amp; Bumper</b> |          |                                                                                                                                                                                                                                                                                                                                                                                  |         |        |
| 6010670                         | O        | <b>Aluminum Space Saver Battery Box LH BOC</b><br>Battery access from side                                                                                                                                                                                                                                                                                                       | 85      | -57    |
| 6040550                         | S        | <b>Aftertreatment Aluminum Non-Slip Cab Entry</b><br>Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.                                                                                                                                                  | 0       | 0      |
| 6121090                         | O        | <b>Steel Bumper Deep Tapered Chromed</b><br>Two tow points                                                                                                                                                                                                                                                                                                                       | -324    | 49     |
| 6132040                         | O        | <b>Omit Front Tow Pin(s)</b>                                                                                                                                                                                                                                                                                                                                                     | -56     | -2     |
| 6132450                         | O        | <b>Heavy Duty External Tow Eye</b>                                                                                                                                                                                                                                                                                                                                               | 607     | 42     |

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



| Sales Code                   | Std/ Opt | Description                                                                                                                                                                                                                                                                                                                                                                                     | \$ List | Weight |
|------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|--------|
| IPO Standard, N/A With FETPO |          |                                                                                                                                                                                                                                                                                                                                                                                                 |         |        |
| <b>Cab &amp; Equipment</b>   |          |                                                                                                                                                                                                                                                                                                                                                                                                 |         |        |
| 6515770                      | O        | <b>Vocational 121 BBC Alum Cab and Metton Hood SFFA</b><br>Stainless steel crown and grille with tilt assist.                                                                                                                                                                                                                                                                                   | 3,756   | -30    |
| 6540160                      | O        | <b>Thermal Insulation Package in Cab</b><br>The thermal insulation package is designed to make the cab thermally efficient in extreme temperatures. The model 520 adds insulation surrounding the doghouse to reduce engine heat transmitted to the cab.                                                                                                                                        | 20      | 2      |
| 6540660                      | O        | <b>SmartSound Cab Insulation Package</b><br>Cab acoustic insulation package for day cabs. Includes insulated inside firewall, top side floor damping, absorber treated kick panels, and insulated backwall and roof structure.                                                                                                                                                                  | 429     | 65     |
| 6700000                      | S        | <b>No Sleeper Selected</b>                                                                                                                                                                                                                                                                                                                                                                      | 0       | 0      |
| 6800330                      | O        | <b>Rubber Fender Lips 4.5" Wide</b>                                                                                                                                                                                                                                                                                                                                                             | 631     | 6      |
| 6913200                      | O        | <b>National HP Driver Seat</b><br>The National HP driver seat provides the latestes techonology in comfort, adjustability and ergonomic support. Includes a wide mounting base.                                                                                                                                                                                                                 | 398     | -6     |
| 6921740                      | S        | <b>Peterbilt ST Non-Adjustable Passenger Seat</b><br>Standard vinyl, no suspension cover, no seat back recline.                                                                                                                                                                                                                                                                                 | 0       | 0      |
| 6930580                      | O        | <b>Drivers Armrests - LH &amp; RH</b>                                                                                                                                                                                                                                                                                                                                                           | 170     | 4      |
| 6930800                      | O        | <b>Black Seat Color IPO Standard Color</b>                                                                                                                                                                                                                                                                                                                                                      | 0       | 0      |
| 6931120                      | O        | <b>Seat Belt Color Orange IPO Standard</b><br>Black                                                                                                                                                                                                                                                                                                                                             | 13      | 0      |
| 6939400                      | S        | <b>Air Ride Driver</b>                                                                                                                                                                                                                                                                                                                                                                          | 0       | 0      |
| 6939420                      | S        | <b>High Back Driver</b>                                                                                                                                                                                                                                                                                                                                                                         | 0       | 0      |
| 6939480                      | O        | <b>Mordura Driver</b>                                                                                                                                                                                                                                                                                                                                                                           | 92      | 0      |
| 6939510                      | S        | <b>Non-Air Ride Passenger</b>                                                                                                                                                                                                                                                                                                                                                                   | 0       | 0      |
| 6939520                      | S        | <b>High Back Passenger</b>                                                                                                                                                                                                                                                                                                                                                                      | 0       | 0      |
| 6939580                      | O        | <b>Mordura Passenger</b>                                                                                                                                                                                                                                                                                                                                                                        | 91      | 0      |
| 6939660                      | S        | <b>Static Riser Under Passenger Seat</b><br>Peterbilt passenger non-adjustable seat.                                                                                                                                                                                                                                                                                                            | 0       | 0      |
| 7000025                      | S        | <b>Steering Wheel With Multi-Function</b><br>Includes Peterbilt logo on horn button , audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.                                                                                                                                                                   | 0       | 0      |
| 7000045                      | O        | <b>High-Visibility Interior Grabhandles, Painted</b><br>Bright yellow interior grabhandle for vocational vehicles.                                                                                                                                                                                                                                                                              | 37      | 0      |
| 7001520                      | S        | <b>Adjustable Steering Column - Tilt/Telescope</b>                                                                                                                                                                                                                                                                                                                                              | 0       | 0      |
| 7037130                      | S        | <b>Prestige Interior - Sterling Gray</b><br>Features single tone dash with tough, scratch resistant materials including soft touch points on top of dash. Top of dash, door panel uppers, and kick panel are charcoal to conceal dirt and mitigate wear. Includes unique technical grained A,B, C & D instrument panels with contoured doorpads, padded fabric headliner and vinyl wall panels. | 0       | 0      |

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



| Sales Code | Std/ Opt | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | \$ List | Weight |
|------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|--------|
|            |          | Superior ergonomics are achieved while maximizing productivity featuring: multiple power ports, (2) coat hooks, header-mounted domelight, power lift driver and passenger windows, LH and RH door mounted map pockets with built-in courtesy lights, driver and passenger dome/reading lights and footwell lighting. Comfort features include automatic temperature HVAC controls, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, rubber flooring, (3) inside sunvisors, integrated "dead pedal, cup holder and map bin in dash. |         |        |
| 7110680    | O        | <b>Exterior Cab Entry Grabhandle</b><br>Textured; NFPA compliant. Available on Day Cab specifications only.                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 175     | 6      |
| 7210540    | S        | <b>Day Cab Rear Window</b><br>Day cab rear window flush to back of cab.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 0       | 0      |
| 7210550    | S        | <b>1-Piece Glass Rear Cab Window Fixed</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 0       | 0      |
| 7230060    | S        | <b>1-Piece Curved Windshield</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 0       | 0      |
| 7230360    | S        | <b>Power Door Locks and Power Window Lifts</b><br>Standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 0       | 0      |
| 7322010    | S        | <b>Combo Fresh Air Heater/Air Conditioner</b><br>With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.                                                                                                                                                                                                                                                                                                                                                              | 0       | 0      |
| 7330880    | O        | <b>Additional Fine Particulate Filter For HVAC Syst</b><br>3 micron filtration. For use in extreme high dust applications. Not available with Ember filter 7330890.                                                                                                                                                                                                                                                                                                                                                                                            | 18      | 1      |
| 7514010    | O        | <b>Peterbilt Aero Rear View Mirror, Motorized</b><br>Includes top mirror with motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.                                                                                                                                                                                                                                                                                                                                | 318     | 3      |
| 7514020    | O        | <b>Aero Rear View Mirror Housing - Body Color</b><br>(Same Color as Vehicle Body)                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 21      | 0      |
| 7514050    | S        | <b>Look Down Mirror Over Passenger Door</b><br>with Black Housing                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 0       | 0      |
| 7610500    | S        | <b>Air Horn Mounted Under Cab</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 0       | 0      |
| 7722120    | O        | <b>ConcertClass, AM/FM, Weatherband, 3.5 Aux</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 463     | 10     |
| 7725740    | O        | <b>Midlevel Speaker Package For Cab</b><br>(4) Speakers                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 121     | 6      |
| 7728040    | O        | <b>Bluetooth Phone and Audio Requires USB Port</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 122     | 0      |
| 7728050    | O        | <b>USB Port</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 51      | 0      |
| 7740220    | O        | <b>Uniden PC78LTX CB Radio Mounted</b><br>Center Of Without weatherband.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 243     | 10     |
| 7743020    | O        | <b>(1) Antenna for Factory Installed</b><br>Or F/O CB, mounted vertical center BOC/BOS.                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 98      | 1      |
| 7788335    | S        | <b>Global Telematics Hardware</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 0       | 0      |
| 7851100    | O        | <b>Stationary Grille w/o Fepto Extension</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 1,264   | 4      |
| 7851480    | S        | <b>Peterbilt Electric Windshield Wipers</b><br>With Intermittent Feature.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 0       | 0      |
| 7852020    | O        | <b>Cab Air Suspension</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 280     | 15     |

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



| Sales Code | Std/ Opt | Description                                                                                                                                                                                                                                                                    | \$ List | Weight |
|------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|--------|
| 7855120    | O        | <b>Bugscreen - Removable External Mounted</b>                                                                                                                                                                                                                                  | 301     | 2      |
| 7900090    | O        | <b>Triangle Reflector Kit, Ship Loose</b><br>Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.                                                                                                                                      | 33      | 13     |
| 7900320    | O        | <b>Fire Extinguisher, Mounted Inboard Driver Seat</b><br>Hazmat approved UL listed/rated ABC                                                                                                                                                                                   | 76      | 8      |
| 7901130    | O        | <b>Backup Alarm (107 DB)</b>                                                                                                                                                                                                                                                   | 135     | 3      |
| 8011410    | O        | <b>Drive Axle #1 Front Oil Temperature Gauge</b><br>52mm round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display. | 96      | 0      |
| 8011420    | O        | <b>Drive Axle #2 Rear Oil Temperature Gauge</b><br>52mm round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.  | 109     | 0      |
| 8011470    | O        | <b>Engine Oil Temperature Gauge</b><br>52mm round, backlit. These physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.        | 5       | 0      |
| 8011850    | O        | <b>Transmission Oil Temperature (Main)</b><br>Located in Digital Cluster Display.                                                                                                                                                                                              | 29      | 0      |
| 8012240    | O        | <b>Guard(s) For Rear Axle Heat Gauge</b>                                                                                                                                                                                                                                       | 69      | 2      |
| 8021800    | S        | <b>Air Filter Restriction Pressure Gauge</b><br>Located in Digital Cluster Display                                                                                                                                                                                             | 0       | 0      |
| 8021810    | S        | <b>Brake Application Air Pressure (Tractor)</b><br>Located in Digital Cluster Display.                                                                                                                                                                                         | 0       | 0      |
| 8022160    | O        | <b>Fuel Filter Restriction Gauge</b><br>52mm Round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.             | 166     | 0      |
| 8070100    | O        | <b>(4) Additional Dash Switches With Wiring</b><br>Located on dash panel C. Availability subject to dash space. Includes 4" 14 gauge wire with butt splice at rear of each additional switch.                                                                                  | 172     | 1      |
| 8070250    | O        | <b>Switch &amp; Wiring For F/O Snow Plow Light Install.</b><br>Switch and wiring for furnished by owner snow plow light installation. J168 on chassis harness.                                                                                                                 | 101     | 0      |
| 8070450    | O        | <b>Engine PTO Hourmeter Gauge</b><br>Located In Digital Cluster Display                                                                                                                                                                                                        | 0       | 0      |
| 8070820    | S        | <b>Engine Percent Torque</b><br>Located in Digital Cluster Display                                                                                                                                                                                                             | 0       | 0      |
| 8070830    | O        | <b>Main Instrumentation Panel</b><br>Digital Cluster 15" Display includes: Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, and Voltmeter.                           | 0       | 0      |
| 8071470    | O        | <b>ABS Off-Road Switch</b><br>Bendix ATC is required on the specification. Off-Road switch allows some wheel slippage prior to ATC activation. Off-Road switch will cause                                                                                                      | 95      | 0      |

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



| Sales Code | Std/ Opt | Description                                                                                                                                                                                                                                                                                                                                                                                                                                      | \$ List | Weight |
|------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|--------|
|            |          | the ATC light to flash, reminding the driver of a condition. Switch should only be used in extreme conditions such as snow, ice or mud.                                                                                                                                                                                                                                                                                                          |         |        |
| 8071900    | O        | <b>Manifold Pressure Gauge</b><br>52mm Round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.                                                                                                                                                                                     | 62      | 2      |
| 8073020    | O        | <b>(4) Additional Electric Over Air Switches</b><br>On/off only, switch has green indicator light, air connections on frame rail under cab. Four accessory solenoid banks with plugs.                                                                                                                                                                                                                                                            | 107     | 2      |
| 8110070    | S        | <b>Headlights Projector Module Pod</b><br>Fender mounted turn signals, projector module low beam, complex reflector high beam, pod mounted                                                                                                                                                                                                                                                                                                       | 0       | 0      |
| 8121170    | O        | <b>(5) Marker Lights, Bus LED Bullet</b>                                                                                                                                                                                                                                                                                                                                                                                                         | 179     | 0      |
| 8131420    | O        | <b>Switch &amp; Wiring For F/O Fog Lights</b><br>With bumper cutouts                                                                                                                                                                                                                                                                                                                                                                             | 165     | 0      |
| 8132215    | O        | <b>(2) LED Strobe Lights Roof Mounted</b><br>(2) LED strobe lights roof mounted on each side of the cab with stainless steel brackets. LED technology provides continual heavy-duty use in the toughest conditions with a weatherproof and vibration resistant design for external use. Offering four times the brightness in a more compact housing, 4.5" shorter and 3" smaller in diameter. Classified as a Class 1 light incandescent light. | 396     | 10     |
| 8133960    | S        | <b>Daytime Running Lights</b><br>The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.                                                                                                                                                                                                                                                                        | 0       | 0      |
| 8140850    | O        | <b>Moveable EOF Crossmember For Mounting Tail Lights</b><br>Square end of frame with or without end of frame crossmember                                                                                                                                                                                                                                                                                                                         | 51      | 2      |
| 8141000    | O        | <b>LED Stop/Turn/Tail, Backup Flange Mounted</b><br>Flange mounted. LED backup and security rings. Tapered end of frame mounted under end of frame crossmember. Mounted inset between rails.                                                                                                                                                                                                                                                     | 108     | 28     |
| 8141150    | O        | <b>Additional LED Turn Signals</b><br>Mounted lower rear corners back of cab / back of sleeper                                                                                                                                                                                                                                                                                                                                                   | 248     | 10     |

#### Paint

|         |   |                                                                                                                                                                                                                                 |      |   |
|---------|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|---|
| 8500710 | S | <b>Standard Paint Color Selection</b>                                                                                                                                                                                           | -200 | 0 |
| 8530770 | S | <b>(1) Color Axalta Two Stage - Cab/Hood</b><br>Base Coat/Clear Coat<br>N85020 A - L0006EY WHITE<br>N85500 CAB ROOF L0006EY WHITE<br>N85300 FENDER L0006EY WHITE<br>N85200 FRAME L0001EA BLACK<br>N85400 HOOD TOP L0006EY WHITE | 0    | 0 |

#### Shipping Destination

#### Options Not Subject To Discount

|         |   |                                                                                 |   |   |
|---------|---|---------------------------------------------------------------------------------|---|---|
| 9400090 | S | <b>Peterbilt Class 8 Standard Coverage</b><br>1 year/100,000 Miles (160,000 km) | 0 | 0 |
|---------|---|---------------------------------------------------------------------------------|---|---|

Price Level: January 1, 2026

100% Complete

Date: August 28, 2026

Deal: PLOW TRUCKS

Quote Number: QUO-1274330-P3T4V9

Printed On: 8/28/2026 11:35:49 AM



| Sales Code           | Std/ Opt | Description                                                                                                                                                            | \$ List | Weight |
|----------------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|--------|
| 9407147              | O        | Fuel Price Index Factor \$483 NET                                                                                                                                      | 483     | 0      |
| 9408626              | O        | SmartLINQ RD - 5YR Sub<br>Cummins Engines                                                                                                                              | 799     | 0      |
| 9408707              | O        | Base Warr: Emissions (CARB Operation)<br>5YR/350K MI - X15 PER/PRO Engine                                                                                              | 3,895   | 0      |
| 9408982              | O        | Vehicle Layout<br>Option is not subject to discount. Fleets will be split prior to build so that the charge is applied to only one unit. Quotes will not reflect this. | 1,500   | 0      |
| <b>Miscellaneous</b> |          |                                                                                                                                                                        |         |        |
| 9409001              | S        | Day Cab / Prestige Interior (DM)                                                                                                                                       | 0       | 0      |
| 9409076              | O        | State Of Registry: Montana                                                                                                                                             | 0       | 0      |
| 9409641              | O        | Model Year 2026 Engine                                                                                                                                                 | 0       | 0      |
| 9409749              | O        | 2024 Series Emissions Engine                                                                                                                                           | 0       | 0      |
| 9409843              | O        | Peterbilt Sourcewell Program Code<br>Applicable with Marketing Programs Only. No CAR allowed                                                                           | 0       | 0      |
| 9485083              | O        | Basic Vehicle (CARB) 5/200<br>5 yrs / 200,000 mi / 320,000 km                                                                                                          | 4,905   | 0      |
| 9487548              | O        | Cummins Prtect Plan+ (5/200) CARB<br>2024 Series X15 Performance/Productivty                                                                                           | 2,200   | 0      |

## Promotions

### Special Requirements

Special Requirement 1 0098170  
Special Requirement 2  
Special Requirement 3  
Special Requirement 4

### Fuel Efficiency Score:

### Order Comments

# K O I S EQUIPMENT COMPANY INC.

DENVER  
5200 Colorado Blvd.  
Commerce City, CO 80022  
Phone: 303-298-7370  
Fax: 303-298-8527

BILLINGS  
2107 Harnish Blvd.  
Billings, MT 59101  
Phone: 406-652-3975  
Fax: 406-652-3744

GREAT FALLS  
1610 River Drive North  
Great Falls, MT 59401  
Phone: 406-452-2757  
Fax: 406-452-2799

DATE 08/28/26  
PAGE 1  
QUOTE NO. 26-17080  
\*\*\* QUOTE \*\*\*

## SOLD TO:

JACKSON GROUP PETERBILT  
3255 NORTH FRONTAGE ROAD  
DAN WEIMER 4066904235  
BILLINGS MT 59101

## SHIP TO:

JACKSON GROUP PETERBILT  
3255 NORTH FRONTAGE ROAD  
DAN WEIMER 4066904235  
BILLINGS MT 59101

| CUSTOMER PO | CUSTOMER NUM | SHIP VIA | SALESMAN | TERMS | CUSTOMER PHONE |
|-------------|--------------|----------|----------|-------|----------------|
| DAN WEIMER  | 99996        | GROUND   | 17       | CASH  | 406-252-5667   |

SOURCEWELL CONTRACT: 033126-AEB


## YELLOWSTONE COUNTY BID SPEC:

SWENSON ABP DUAL PURPOSE BODY  
16' STAINLESS STEEL BODY  
CHAIN DRIVEN UNIT  
LIVE BOTTOM WITH BOLT ON CONVEYOR COVER 1/4" AR450  
1/4" MIN FLOOR THICKNESS AR450  
FRONT DISCHARGE  
SPINNER MOUNTED DRIVERS SIDE BEHIND THE CAB OUTSIDE OF FRAME RAIL  
REAR FACING GREEN AND RED STROBES  
LIGHT PACKAGE PER SPEC  
STAINLESS STEEL FOLD-UP LADDER  
LED LIGHT PACKAGE PER SPEC  
REAR HITCH  
60,000LB CAPACITY  
PLUMBED FOR TRAILER BRAKES  
7-WAY PLUG  
CHIP SPREADER BAR  
FORCE AMERICA HYDRAULIC CONTROLS 6100 G5  
VT35 TANK VALVE COMBO

HENKE/WAUSAU 12' ROAD WARRIOR SNOW PLOW  
FRONT MOUNT QUICK ATTACH  
BREAK AWAY  
3-CARBIDE CUTTING EDGES

INSTALLED COMPLETE-----

\*\*\* CONTINUED NEXT PAGE \*\*\*





## SHIFT TO THE HIGHER STANDARD



### HENKE'S MODULAR PLOW SYSTEM - Flexibility to build the best plow for your application

With **over 100 years of experience making snow plows**, Henke has developed a standardized plow line that gives you the flexibility to build the plow you need. By combining different options for height, width, profile, pushframe, trip, hitch, and running gear, you can easily create a highly customized "standard" plow.

- ▶ Henke's moldboards with chain style level lift (or optional sliding level lift) **keeps the plow level** while our **integral snow shield prevents snow from blowing over the top** of the moldboard.
- ▶ Henke's **Grade 50 Steel is 39% stronger** than A-36 Steel.
- ▶ Henke's **Road Safe pushframe provides maximum strength** and prevents bottom angle bending. **Cylinders are located above the pushframe for protection** against road debris and ease of maintenance.



*From the urban core to the steepest mountain passes, Henke's Road Warrior Plow will conquer your toughest challenges*

|   | SELECT:                                                                                      | STYLES                                                                                                                                                                                                            | MATERIALS                                                                                                                                                                                  | LENGTHS (ft)                                                                                                                   | HEIGHTS         |
|---|----------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|-----------------|
| 1 | MOLDBOARDS                                                                                   | Straight<br>Expressway<br>Funnel/One-Way                                                                                                                                                                          | Grade 50 Steel<br>304 Stainless<br>Poly-Lined Steel                                                                                                                                        | 10<br>11<br>12                                                                                                                 | Varies by Style |
|   |                                                                                              | STYLES                                                                                                                                                                                                            | LENGTHS                                                                                                                                                                                    | NOTES                                                                                                                          |                 |
| 2 | PUSHFRAMES                                                                                   | Road Safe**<br>Tube Table**<br>Parallel Lift**                                                                                                                                                                    | Standard: 119.5" 6 Ribs<br>Heavy Duty: 119.5", 8 Ribs                                                                                                                                      | *Road Safe frame prevents bottom angle bending. Cylinders above frame.<br>**Not available with all moldboard shapes and sizes. |                 |
|   |                                                                                              | STYLES                                                                                                                                                                                                            | DESCRIPTION                                                                                                                                                                                |                                                                                                                                |                 |
| 3 | TRIPS<br><br>(Not all trips are available with every moldboard size and pushframe selection) | ECT<br>EST<br>EXT<br>SLT<br>SSTE                                                                                                                                                                                  | External Compression - Spring<br>Enclosed Springs - EST (Single) or DEST (Dual)<br>Extension Spring - 6 Springs or 8 Springs<br>Slotted Trip - Spring-in-Spring<br>Square Spring Trip Edge |                                                                                                                                |                 |
| 4 | LIFT SYSTEMS                                                                                 | Standard Lift: 2 Chain level lift design<br>Sliding Level Lift: Improved Performance as plow is angled<br>Parallel Lift: True level lifting as plow is angled and raised or lowered                               |                                                                                                                                                                                            |                                                                                                                                |                 |
| 5 | OPTIONS: <i>Many options are available. A few common ones are listed.</i>                    | Various Wear Components; Various Running Gear (Runner Shoes, Steel Wheels, Pneumatic Running Gear, Mushroom Shoes - standard or spring loaded)<br>Single or Dual Mouse Ears; Mailbox Cut; Jack Stand; Rod Markers |                                                                                                                                                                                            |                                                                                                                                |                 |